



# 14X12X6 SOLID DOOR LATCH ENCLOSURE WITH INTEGRATED 4-ELEMENT 3/4 DBI OMNI ANTENNA WITH RPTNC

ATS-14126P-S-L-CG-UBPTB-INTOO-34-4RPTP



## ELECTRICAL SPECIFICATIONS

- Solution comes pre-drilled and ready for installation
- Integrated 4-Element omni antenna with RPTNC plugs already installed on the enclosure bottom
- Universal backplate
- Cord grip installed on the enclosure bottom



## SOLUTIONS COMPONENTS

- 14x12x6 Nonconfigured Polycarbonate enclosure with Solid Door and Latch Lock
- 2.4/5 GHz 3/4 dBi 4-Element Indoor/Outdoor Omni Antenna with RPTNC connectors
- Nylon Cord Grip - Grey
- Universal Aluminum Backplate with mounting hardware



## ENCLOSURE SPECS

- Material: Polycarbonate
- Door Type: Solid
- Lock Type: Latch with Integrated Pad-Lockable Hasp
- Environmental Protection: NEMA 6P, 4X, 4, 3R, 122
- Ingress Protection: IP68



## ANTENNA SPECS

Frequency Range: 2.4-2.5 / 4.9-5.85 GHz  
Gain: 3/4 dBi  
Polarization: Vertical  
Horizontal Beamwidth: 360°  
Vertical Beamwidth: 75° / 50°  
VSWR: <2.0:1  
Isolation: >20dB  
Impedance: 50 Ω  
Max Input Power: 100W

Radome Material: ASA  
Connector: RPTNC Plug  
Cable Length: 36" (910mm)  
Cable Type: RG58  
Operating Temperature: -40 to 149°F (-40 to 65°C)