




## FEATURES

- Door is easily removed and can be installed to open in any direction with our innovative spring hinge system
- AP installs using the included ceiling tile grid clip shipped with the AP onto an integrated mounting plate with no tools
- Key lock for security
- Includes integrated tabs for securing enclosure mount to permanent building structure
- Shallow back box (1.5") allows installation into the tightest ceiling clearances



## BENEFITS

- Easy to Install
- No ceiling tile grid modification necessary (if mounting into a 2'x2' grid)
- Service the AP without removing the enclosure mount from ceiling
- Lightweight aluminum design reduces ceiling strain and load
- Simple, one person installation
- Blends seamlessly into ceiling
- No tools required for installation




## MOUNT SHIPS WITH

- 2x2 Suspended Ceiling Tile Enclosure Mount with installed door
- Cord Grip
- Key



Integrated mounting tabs on two sides



Spring Hinge



Key Lock



Integrated Mounting Plate, Cord Grip and  
Repositionable Door



# CISCO® AP SUSPENDED CEILING TILE ENCLOSURE MOUNT (CATALYST® 9130 STYLE) ATS-CT-CISCO8-2X2



## MECHANICAL SPECIFICATIONS

Dimensions: 23.75" x 23.75" x 1.5" (603.25mm x 603.25mm x 38.1mm)  
Weight (without AP): 3.75 lb (1.70 kg)  
Material: Aluminum. Steel (Key & Latch Lock)  
Color: White  
Lock: Key Lock  
Installation: Suspended Ceiling (includes tabs for securing to building structure)  
Equipment Installation: AP Mounting Feet onto Included Mounting Bracket  
Load Capacity: 5.5 lbs. (2.5 kg.)



## ENVIRONMENTAL SPECIFICATIONS

Installation Environment: Indoor



## STANDARDS, TESTING AND CERTIFICATIONS

Designed to meet NEC300-22 and 300-23 to mount the Cisco AP in plenum/air handling areas  
UL2416: Investigation of the enclosure system covers the enclosure only.



## WARRANTY

2 Year Limited Warranty