

GENERAL DESCRIPTION

Canfield Connector now offers many of our great multi-conductor control wire options for bulk purchasing availability. The same wire we use on our industry leading connector and sensors lines is now available in 50, 100, 500, 1,000, 2,500 and 5,000 feet reels. Whether you are working on a large-scale project or simply need a lot of wire on hand for future jobs, our bulk purchasing options make it easy and affordable to get the wire you need.



BULK AND CUT TO LENGTH MULTI-CONDUCTOR CABLE

ORDERING INFORMATION

20 AWG, PVC, US, Black Jacket (Used with 5J 9.4mm)

Length (Ft.)	3 Conductor Part Number
50'	W203U-PVC0-10790-50
100'	W203U-PVC0-10790-100
500'	W203U-PVC0-10790-500
1000'	W203U-PVC0-10790-1000
2500'	W203U-PVC0-10790-2500
5000'	W203U-PVC0-10790-5000
Conductors	 Black, White, Green

18 AWG, PVC, US, Black Jacket (Used with 5J MINI / ISO)

Length (Ft.)	3 Conductor Part Number	4 Conductor Part Number
50'	W183U-PVC0-10830-50	W184U-PVC0-10840-50
100'	W183U-PVC0-10830-100	W184U-PVC0-10840-100
500'	W183U-PVC0-10830-500	W184U-PVC0-10840-500
1000'	W183U-PVC0-10830-1000	W184U-PVC0-10840-1000
2500'	W183U-PVC0-10830-2500	W184U-PVC0-10840-2500
5000'	W183U-PVC0-10830-5000	W184U-PVC0-10840-5000
Conductors	 Black, White, Green	 Black, White, Green, Red

24 AWG, PVC, US, Black Jacket (Used with M8, M12)



Length (Ft.)	3 Conductor Part Number	4 Conductor Part Number	5 Conductor Part Number
50'	W243U-PVC0-12380-50	W244U-PVC0-12390-50	W245U-PVC0-12400-50
100'	W243U-PVC0-12380-100	W244U-PVC0-12390-100	W245U-PVC0-12400-100
500'	W243U-PVC0-12380-500	W244U-PVC0-12390-500	W245U-PVC0-12400-500
1000'	W243U-PVC0-12380-1000	W244U-PVC0-12390-1000	W245U-PVC0-12400-1000
2500'	W243U-PVC0-12380-2500	W244U-PVC0-12390-2500	W245U-PVC0-12400-2500
5000'	W243U-PVC0-12380-5000	W244U-PVC0-12390-5000	W245U-PVC0-12400-5000
Conductors	 Blue, Brown, Black	 Blue, Brown, Black, White	 Blue, Brown, Black, White, Gray

ORDERING INFORMATION

22 AWG, PVC, US, Gray Jacket (Used with 7000)

Length (Ft.)	2 Conductor Part Number	3 Conductor Part Number
50'	W222U-PVC0-10000-50	W223U-PVC0-11730-50
100'	W222U-PVC0-10000-100	W223U-PVC0-11730-100
500'	W222U-PVC0-10000-500	W223U-PVC0-11730-500
1000'	W222U-PVC0-10000-1000	W223U-PVC0-11730-1000
2500'	W222U-PVC0-10000-2500	W223U-PVC0-11730-2500
5000'	W242U-PVC0-10000-5000	W243U-PVC0-11730-5000
Conductors	 Red, Black	 Red, Black, White

24 AWG, PVC, US, Gray Jacket (Used with 8000)

Length (Ft.)	2 Conductor Part Number	3 Conductor Part Number
50'	W242U-PVC0-28302-50	W243U-PVC0-28303-50
100'	W242U-PVC0-28302-100	W243U-PVC0-28303-100
500'	W242U-PVC0-28302-500	W243U-PVC0-28303-500
1000'	W242U-PVC0-28302-1000	W243U-PVC0-28303-1000
2500'	W242U-PVC0-28302-2500	W243U-PVC0-28303-2500
5000'	W242U-PVC0-28302-5000	W243U-PVC0-28303-5000
Conductors	 Brown, White	 Brown, White, Green

26 AWG, PVC, US, Black Jacket (Used with 9D)

Length	2 Conductor Part Number	3 Conductor Part Number
50'	W262U-PVC0-10430-50	W263U-PVC0-10420-50
100"	W262U-PVC0-10430-100	W263U-PVC0-10420-100
500"	W262U-PVC0-10430-500	W263U-PVC0-10420-500
1000"	W262U-PVC0-10430-1000	W263U-PVC0-10420-1000
2500"	W262U-PVC0-10430-2500	W263U-PVC0-10420-2500
5000"	W262U-PVC0-10430-5000	W263U-PVC0-10420-5000
Conductors	 Blue, Brown	 Blue, Brown, Black

TECHNICAL DATA

Voltage Rating	300V
Temperature Range	-20° to +80°C
Flame Rating	VW-1/FT1
Approvals	UL

Ordering Example: W262U-PVC0-10430-50
26 AWG, PVC, US, Black Jacket, 50', 2 Conductor