



**SubseaLink**



- Manufactured for use in subsea or submersible projects.
- On board data-logging option.
- Pressure tested to depth of 6,562 ft.
- SubConn connector.
- Environmental protection IP68/NEMA6P.
- Output options include mV/V to the Crosby SP Handheld Plus, 4-20mA or 0-10v analog to a PLC, data-logger or The Multi Operation Survey System (MOSS), RS485 or an integral data-logger storing up to one million readings and powered by an internal battery.
- Constructed from 17-4PH stainless steel.
- Designed to fit with The Crosby Group ROV shackles.
- Option for ROV mounting on the SL body itself.
- Output: Options for: mV/V / 4-20mA / 0-10v / RS485 or internal data logger.
- Design Factor: 5:1
- Operating Temperature: 14°F to 122°F.
- Accuracy: ±0.1% of full scale.
- Max depth of use: 6,562 ft.
- Material: 17-4 PH Stainless steel.
- MTBF to WLL: Typically 50 million cycles.
- Elongation: Typically <0.016in / at WLL.



**Straightpoint SubseaLink (SL)**

Stock No.	Model	Capacity (lb)	Weight (lb)	Dimensions (in)						Crosby Shackle	
				A	B	C	D	ØE	F		
2789352	SL6T5	14,300	15	3.74	9.45	7.09	0.98	1.18	2.87	G2130	1019533
2789353	SL12T	26,000	23	3.94	11.81	7.87	1.57	1.57	3.46	G2130	1019597
2789354	SL25T	55,000	34	5.12	13.78	9.06	1.77	2.17	3.66	G2130	1019659
2789355	SL35T	77,000	49	5.91	15.75	9.84	1.97	2.36	3.86	G2130	1019677
2789356	SL55T	120,000	75	6.61	17.72	10.24	2.56	2.95	4.45	G2130	1021156
2789357	SL85T	185,000	101	7.48	19.29	11.42	2.95	3.46	4.84	G2130	1021174
2789358	SL120T	260,000	148	8.66	21.65	13.19	3.39	3.94	5.28	G2140	1021192

Data-logger Measurement Rate	Days
1 per second	10
1 per 30 seconds	57
1 per minute	729
1 per 2 minutes	1445
1 per 30 minutes	3423
1 per hour	3600
1 per 2 hours	3694
1 per 8 hours	3769