Eaton 5P1500R-L

F:T.N

Catalog Number: 5P1500R-L

Eaton 5P UPS, 1U, 1440 VA, 1100W, 5-15P Input, Outputs: (5) 5-15R, 120V, Rackmount/Wallmount, Lithium-ion battery, true sine wave, network card optional

General specifications

Product Name Eaton 5P UPS

UPC 743172091901

Product Height 1.7 in

Product Weight 35 lb

Certifications

UL 1778 cULus Listed IEC 62040-2:2006 Cat C2 CE Catalog Number 5P1500R-L

Product Length/Depth 21.8 in

Product Width 17.4 in

Compliances

RoHS Compliant REACH



Battery

Runtime graph

\$row.attributeValue.cdata

Battery management

Integrated battery management system (BMS) for temperature regulation and life cycle monitoring

Battery replacement

User replaceable

Battery type

Lithium-ion

Extended battery capability

None; See Eaton 5PX UPS for extended runtimes options

Electrical output

Receptacle

(5) 5-15R

Topology

Line-interactive

Wattage

1100 W

VA rating

1440 VA

Output waveform

Sine wave

Voltage

120V

Output nominal voltage

120V default (100/120/125V)

Output voltage range 102-132 Vac

102-132 Val

Feed type

1

Electrical input

Input connection

5-15P

Input cord length

6 ft

Input nominal voltage 120V default (100/110/120/125V)

Input voltage range 89-151 Vac (adjustable to 70-153 Vac)

Nominal frequency

50-60 Hz

Input frequency range 47-70 Hz (50 Hz system), 56.5-70 Hz (60 Hz system), 40-70 Hz in low-sensitivity mode

Communications

Communication

RS-232 (RJ45) ports; USB port as standard (HID). 6-foot RS-232 and USB cables included

Expansion slots

One slot; Gigabit Network Card (Network-M2) is optional

Software compatibility Eaton Intelligent Power Manager

User interface LCD graphical display

Environmental

Altitude Up to 10,000 ft (3000m) without de-rating

BTU Rating

10 10,000 it (3000iii) with

Online: 113, Battery 714

Noise level <45 dB at 1 meter

Relative humidity 0-85% non-condensing

Temperature range 0° to 40°C (32° to 104°F)

Additional specifications

Special features

ROO/RPO: Rear terminal block connector for remote on/off and power off

Form factor

Rack

Rack size

1U

Rack mounting kit

Yes

Efficiency

98%

Package contents

UPS Quick start guide Safety instructions USB communciation cable RS-232 serial communication cable 4-post rail and wallmount kit

Warranty and support

Standard factory warranty

5-YEAR FACTORY WARRANTY -5 years -Parts, electronics, and batteries coverage -Standard ground shipping

-Technical support

Resources

Application notes Eaton single-phase UPS battery tech brief

Brochures

Eaton Lithium-ion battery benefits

5-series UPS overview brochure

Eaton 5P Lithium-ion rackmount UPS brochure

Drawings Eaton 5P UPS visio stencils

Eaton 5P1500R-L drawing

Manuals and user guides

Eaton 5P UPS quick start guide

Installation and user guide: 5P1500R-L

Specifications and datasheets

Eaton Specification Sheet - 5P1500R-L

Warranty guides



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com © 2024 Eaton. All Righ Reserved.

Eaton is a registered trademark.

Eaton.comAll other trademarks are© 2024 Eaton. All Rightsproperty of their respectiveReserved.owners.



Eaton.com/socialmedia