# Eaton 5P1500RT

# Catalog Number: 5P1500RT

Eaton 5P UPS, 1440 VA, 1440 W, 5-15P input, Outputs: (8) 5-15R, 120V

# General specifications

Product Name Catalog Number
Eaton 5P UPS 5P1500RT

UPC Product Length/Depth

743172039620 20.6 in

Product Height Product Width

3.4 in 17.4 in

Product Weight Warranty

65 lb 3 year on electronics, 3 year on batteries

with registration

Compliances Certifications

FCC Part 15 Class A Subpart B Sections cUL Listed 15.107b , 15.109b UL 1778

UL 497A UL Listed





# Battery

#### Runtime graph

#### Battery management

ABM technology (3-stage charging extends battery service life by 50% and provides advance warning for battery replacement)

#### Battery replacement

User replaceable

#### Battery type

Sealed, lead-acid

#### Extended battery capability

None; See Eaton 5PX UPS for extended runtimes options

# Electrical output

#### Receptacle

(8) 5-15R

#### **Topology**

Line-interactive

#### Wattage

1440 W

#### VA rating

1440 VA

#### Output waveform

Sine wave

#### Voltage

120V

#### Output power factor

1

#### Output nominal voltage

120V default (100/120/125V)

#### Output voltage range

102-132 Vac

#### Feed type

1

# Electrical input

#### Input connection

5-15P

# Input cord length

8 ft

#### Input nominal voltage

120V default (100/110/120/127V)

#### Input voltage range

89-151 Vac (adjustable to 70-153 Vac)

#### Nominal frequency

50-60 Hz

#### Input frequency range

 $47\mbox{-}70~\mbox{Hz}$  (50 Hz system), 56.5-70 Hz (60 Hz system), 40 Hz in low-sensitivity mode

# Communications

#### Communication

1 USB HID compliant port + 1 RS232 serial port and relay contacts (USB and RS232 ports cannot be used simultaneously)

#### **Expansion slots**

One slot; Network Card-MS is optional

#### Software compatibility

Eaton Intelligent Power Manager

#### User interface

LCD graphical display

# Environmental

Altitude

#### Input power factor

1

Up to 10,000 ft (3000m) without de-rating

#### **BTU Rating**

Online: 305, Battery: 2047

#### Noise level

<45 dB at 1 meter

#### Relative humidity

20-95% non-condensing

#### Temperature range

0° to 40°C (32° to 104°F)

# Additional specifications

#### Form factor

Rack/tower

#### Efficiency

98%

# Warranty and support

#### Standard factory warranty

3-YEAR FACTORY

WARRANTY w/

REGISTRATION

- -3 years
- -Parts, electronics, and

batteries coverage

- -Standard ground shipping
- -Technical support

# Extended service plans

ADVANCED DEPOT

**EXCHANGE** 

-5-YEAR DEPOT REPAIR:

5SW5Y-1750UC

-Expedited parts coverage

for 5 years

-Parts, electronics and UPS

batteries coverage

- -Next business day shipping
- -Technical support

5-YEAR ON-SITE PLAN:

WFLN75XX-2509UC

- On-site parts and labor

coverage for years 5

- Parts, electronics and UPS

batteries coverage

- 24x7 on-site labor

coverage, next-day

response

- Next-day shipping
- Technical support

#### Resources

#### **Brochures**

Eaton-5PRackmount-UPS-brochure-BR153009EN.pdf

5-series UPS overview brochure

Eaton 5P Tower UPS brochure

# **Drawings**

Eaton 5P UPS visio stencils

Eaton 5P UPS 3D drawings

#### Manuals and user guides

Installation and user manual: 5P1500RT, 5P2200RT, 5P2200, 5P3000RT, 5P3000

#### Specifications and datasheets

Eaton Specification Sheet - 5P1500RT



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia