

Eaton 5P3000

Catalog Number: 5P3000

Eaton 5P UPS, Tower, 3000 VA, 2700 W, L5-30P input, Outputs: (6) 5-20R; (1) L5-30R, 120V, Tower, true sine wave, network card optional



General specifications

| | |
|---|--|
| Product Name | Catalog Number |
| Eaton 5P UPS | 5P3000 |
| UPC | Product Length/Depth |
| 743172039644 | 25.5 in |
| Product Height | Product Width |
| 17.4 in | 3.4 in |
| Product Weight | Warranty |
| 81 lb | 3 year on electronics, 3 year on batteries with registration |
| Compliances | Certifications |
| FCC Part 15 Class A Subpart B Sections cUL Listed | |
| 15.107b , 15.109b | UL 497A |
| FCC Part 15 | UL 1778 |

Battery

[Runtime graph](#)

View runtime graph

[Battery management](#)

ABM technology (3-stage charging extends battery service life by 50% and provides advance warning for battery replacement)

[Battery replacement](#)

User replaceable

[Battery type](#)

Sealed, lead-acid

[Extended battery capability](#)

None; See Eaton 5PX UPS for extended runtimes options

Electrical output

[Receptacle](#)

(6) 5-20R; (1) L5-30R

[Topology](#)

Line-interactive

[Wattage](#)

2700 W

[VA rating](#)

3000 VA

[Output waveform](#)

Sine wave

[Voltage](#)

120V

[Output power factor](#)

0.9

[Output nominal voltage](#)

120V default (100/120/125V)

[Output voltage range](#)

102-132 Vac

[Output frequency](#)

50/60 Hz

[Feed type](#)

1

Electrical input

[Input connection](#)

L5-30P

[Input cord length](#)

10 ft

[Input nominal voltage](#)

120V default (100/110/120/127V)

[Input voltage range](#)

89-151 Vac (adjustable to 70-153 Vac)

[Nominal frequency](#)

50-60 Hz

Communications

[Communication](#)

1 USB HID compliant port + 1 RS232 serial port and relay contacts (USB and RS232 ports cannot be used simultaneously)

[Expansion slots](#)

One slot; Gigabit Network Card (Network-M2) is optional

[Software compatibility](#)

Eaton Intelligent Power Manager

[User interface](#)

LCD graphical display

Input frequency range

47-70 Hz (50 Hz system), 56.5-70 Hz (60 Hz system), 40 Hz in low-sensitivity mode

Input power factor

0.9

Environmental

Altitude

Up to 10,000 ft (3000m) without de-rating

BTU Rating

Online: 305, Battery: 2047

Noise level

<50 dB at 1 meter

Relative humidity

20-95% non-condensing

Temperature range

0° to 40°C (32° to 104°F)

Additional specifications

Form factor

Tower

Efficiency

97%

Package contents

5P UPS
User manual CD
Intelligent Power Software
Suite CD
Quick start guide
USB cable
RS-232 serial cable

Warranty and support

Standard factory warranty

3-YEAR FACTORY
WARRANTY w/
REGISTRATION
-3 years
-Parts, electronics, and
batteries coverage
-Standard ground shipping
-Technical support

Extended service plans

ADVANCED DEPOT
EXCHANGE
-5-YEAR DEPOT REPAIR:
5SW5Y-3000UC
-Expedited parts coverage
for 5 years
-Parts, electronics and UPS
batteries coverage
-Next business day shipping
-Technical support
5-YEAR ON-SITE PLAN:
WFLN75XX-6009UC
- On-site parts and labor
coverage for years 5
- Parts, electronics and UPS
batteries coverage
- 24x7 on-site labor

coverage, next-day
response
- Next-day shipping
- Technical support

Resources

Brochures

[5-series UPS overview brochure](#)

Drawings

[Eaton 5P UPS 3D drawings](#)

[Eaton 5P UPS visio stencils](#)

Manuals and user guides

[Installation and user manual: 5P1500RT, 5P2200RT, 5P2200, 5P3000RT, 5P3000](#)

Specifications and datasheets

[Eaton Specification Sheet - 5P3000](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia