

Eaton 5P3000RT

Catalog Number: 5P3000RT

Eaton 5P UPS, 3000 VA, 2700 W, L5-30P input, Outputs: (6) 5-20R; (1) L5-30R, 120V, Rack/tower, true sine wave, network card optional

General specifications



Product Name

Eaton 5P UPS

Catalog Number

5P3000RT

UPC

743172039668

Product Length/Depth

640 mm

Product Height

88.9 mm

Product Width

450 mm

Product Weight

36.8 kg

Warranty

3 year on electronics, 3 year on batteries with registration

Compliances

FCC Part 15 Class A Subpart B Sections 15.107b , 15.109b

Certifications

UL 497A
UL 1778
cUL Listed
UL Listed



Powering Business Worldwide

Battery

Runtime graph

View runtime graph

Battery management

ABM technology (3-stage charging extends battery service life by 50% and provides advance warning for battery replacement)

Battery replacement

User replaceable

Battery type

Sealed, lead-acid

Extended battery capability

None; See Eaton 5PX UPS for extended runtimes options

Electrical output

Receptacle

(6) 5-20R; (1) L5-30R

Topology

Line-interactive

Wattage

2700 W

VA rating

3000 VA

Output waveform

Sine wave

Voltage

120V

Output power factor

0.9

Output nominal voltage

120V default (100/120/125V)

Output voltage range

102-132 Vac

Output frequency

50/60 Hz

Feed type

1

Electrical input

Input connection

L5-30P

Input cord length

10 ft

Input nominal voltage

120V default (100/110/120/127V)

Input voltage range

89-151 Vac (adjustable to 70-153 Vac)

Input frequency range

47-70 Hz (50 Hz system), 56.5-70 Hz (60 Hz system), 40 Hz in low-sensitivity mode

Communications

Communication

1 USB HID compliant port + 1 RS232 serial port and relay contacts (USB and RS232 ports cannot be used simultaneously)

Expansion slots

One slot; Gigabit Network Card (Network-M2) is optional

Software compatibility

Eaton Intelligent Power Manager

User interface

LCD graphical display

Input power factor

0.9

Environmental

Altitude

Up to 10,000 ft (3000m) without de-rating

BTU Rating

Online: 305, Battery: 2047

Noise level

<50 dB at 1 meter

Relative humidity

20-95% non-condensing

Temperature range

0° to 40°C (32° to 104°F)

Additional specifications

Form factor

Rack/tower

Efficiency

97%

Warranty and support

Standard factory warranty

- 3-YEAR FACTORY WARRANTY w/ REGISTRATION
- 3 years
- Parts, electronics, and batteries coverage
- Standard ground shipping
- Technical support

Extended service plans

- ADVANCED DEPOT EXCHANGE
- 5-YEAR DEPOT REPAIR: 5SW5Y-3000UC
- Expedited parts coverage for 5 years
- Parts, electronics and UPS batteries coverage
- Next business day shipping
- Technical support
- 5-YEAR ON-SITE PLAN: WFLN75XX-6009UC
- On-site parts and labor coverage for years 5
- Parts, electronics and UPS batteries coverage
- 24x7 on-site labor

coverage, next-day
response
- Next-day shipping
- Technical support

Resources

Brochures

[Eaton 5P Tower UPS brochure](#)

[5-series UPS overview brochure](#)

Drawings

[Eaton 5P UPS 3D drawings](#)

[Eaton 5P UPS visio stencils](#)

Manuals and user guides

[Installation and user manual: 5P1500RT, 5P2200RT, 5P2200,
5P3000RT, 5P3000](#)

Specifications and datasheets

[Eaton Specification Sheet - 5P3000RT](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights
Reserved.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)