

# Eaton 9PX1500RTN

Catalog Number: 9PX1500RTN

Eaton 9PX UPS, 2U, 1500 VA, 1350 W, 5-15P input, Outputs: (8) 5-15R, 120V, Network card

## General specifications



**Product Name**  
Eaton 9PX UPS

**Catalog Number**  
9PX1500RTN

**UPC**  
743172081629

**Product Length/Depth**  
17.7 in

**Product Height**  
3.4 in

**Product Width**  
17.3 in

**Product Weight**  
42.5 lb

**Warranty**  
3 year limited

**Compliances**  
IEC 62040-2 Cat C1  
CISPR22 Class B  
FCC part 15 Class B  
VCCI Class B  
CE Marked

**Certifications**  
cULus Listed  
NOM

## Battery

### Runtime graph

[View runtime graph](#)

### Battery management

ABM technology (3-stage charging extends battery service life by 50% and provides advance warning for battery replacement)

### Battery replacement

Hot-swappable internal batteries and extended battery modules (EBMs)

### Battery type

Sealed, lead-acid

### Extended battery capability

Add up to 4 extended battery modules (EBM). Part number 9PXEBM48RT

## Electrical output

### Receptacle

(8) 5-15R

### Topology

Online/Double-conversion

### Wattage

1350 W

### VA rating

1500 VA

### Output waveform

True sine wave

### Voltage

120V

### Output power factor

0.9

### Output nominal voltage

120V default (100/110/120/125V)

### Output voltage range

±1% steady-state

### Output frequency

50/60 Hz

## Electrical input

### Input connection

5-15P 4

### Input cord length

8 ft

### Input nominal voltage

120V default (100/110/120/125V)

### Input frequency range

60 Hz: 50–70 Hz, 50 Hz: 40–60 Hz

### Input power factor

>0.99 typical

## Communications

### Communication

Web/SNMP in MiniSlot expansion port + 1 USB port + 1 serial RS232 port + 1 mini-terminal block for remote ON/OFF + 1 mini-terminal block for remote power off + 1 mini-terminal block for output relay Communication slot

### Expansion slots

(1) Mini-Slot (MS) expansion port with Gigabit Network Card (NETWORK-M2) included

### Ethernet interface

Yes

### Includes network card

Yes

### Software compatibility

Intelligent Power Software Suite

#### User interface

Graphical display, 5-button programmable menu

## Environmental

#### Altitude

0-1500m (0° to 40°C), 1500-3000m (0° to 35°C)

#### BTU Rating

Online: 512, Battery: 897

#### Noise level

<40 dB at 1 meter

#### Relative humidity

0-96% non-condensing

#### Temperature range

0° to 40°C (32° to 104°F)

## Additional specifications

#### Special features

Gigabit Network Card (NETWORK-M2) included

#### Form factor

Rack/tower

#### Rack size

2U

#### Rack mounting kit

Yes

#### Efficiency

90%

#### Package contents

9PX1500RTN UPS  
Gigabit Network Card  
(Network-M2)  
4-post rail kit  
Safety manual  
User manual  
Tower pedestals  
RS-232 serial cable  
USB cable  
Intelligent Power Software  
Suite CD

#### Internal bypass

Yes

## Warranty and support

#### Standard factory warranty

3-YEAR FACTORY  
WARRANTY

- 3 years
- Parts, electronics and  
batteries coverage
- Standard ground shipping
- Technical support

#### Extended service plans

ADVANCED DEPOT  
EXCHANGE

- 5-year depot repair:  
9SW5Y-1500UC
- Expedited parts coverage  
for 5 years
- Parts, electronics and UPS  
batteries coverage
- Next business day  
shipping

- Technical support  
5-YEAR ON-SITE PLAN:  
WFLN75XX-2509UC

- On-site parts and labor  
coverage for years 5
- Parts, electronics and UPS  
batteries coverage
- 24x7 on-site labor

coverage, next-day  
response  
- Next-day shipping  
- Technical support

## Resources

### Brochures

[Eaton 9PX 700-3000 VA UPS brochure](#)

### Drawings

[Battery Integration System Pro-E drawing](#)

[Eaton 9PX UPS 700-1500 VA 120V outline drawing](#)

[Eaton 9PX UPS 700-1500 VA technical drawing](#)

### Manuals and user guides

[9PX 700-3000 VA 2U UPS user guide](#)

[9PX battery integration system user guide](#)

[9PX 2-post rack kit user guide](#)

### Specifications and datasheets

[9PX 700-3000 VA UPS technical specification](#)

[Eaton 9PX UPS guide specification: 700-3000 VA](#)

[Eaton Specification Sheet - 9PX1500RTN](#)



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)