Eaton 9PX5KTF5

Catalog Number: 9PX5KTF5

Eaton 9PX UPS, Network card included, 6U, 5000 VA, 4500 W, L6-30P input, Outputs: (18) 5-20R, (2) L6-20R, (1) L6-30R, 208V

General specifications

Product Name Eaton 9PX UPS

UPC 743172039774

Product Height 10.2 in

Product Weight 201 lb

Certifications

cULus Listed IEC 62040-2:2006 Cat C2 NOM ENERGY STAR certified Catalog Number 9PX5KTF5

Product Length/Depth 28.4 in

Product Width 17.3 in

Compliances

CE Marked FCC Part 15 CISPR22 Class A / FCC part 15 Class A





Battery

Runtime graph

View runtime graph

Battery management

ABM technology (3-stage charging extends battery service life by 50% and provides advance warning for battery replacement)

Battery replacement

Hot-swappable internal batteries and extended battery modules (EBMs)

Battery type Sealed, lead-acid

Extended battery capability

Add up to 4 extended battery modules (EBM). Part number 9PXEBM180RT

Electrical output

Receptacle

(18) 5-20R, (2) L6-20R, (1) L6-30R, Hardwire (200-240V)

Topology

Online/Double-conversion

Wattage

4500 W

VA rating

5000 VA

Output waveform

True sine wave

Voltage

120/208V

Output power factor

0.9

Output nominal voltage 208V default (200/208/220/230/240V)

Output voltage range

±1% steady-state

Output frequency 50/60 Hz

Electrical input

Input connection L6-30P

Input cord length

6 ft

Input nominal voltage 208V default (200/208/220/230/240V)

Input frequency range 60 Hz: 50–70 Hz, 50 Hz: 40–60 Hz

Input power factor

>0.99 typical

Communications

Communication

Web/SNMP in MiniSlot expansion port + 1 USB port + 1 serial RS232 port + 1 mini-terminal block for remote ON/OFF + 1 miniterminal block for remote power off + 1 mini-terminal block for output relay Communication slot

Expansion slots

(1) Mini-Slot (MS) expansion port with Gigabit Network Card (NETWORK-M2) included

Ethernet interface

Yes

Includes network card Yes

Software compatibility

Intelligent Power Software Suite

User interface

Graphical display, 5-button programmable menu

Environmental

Altitude

<1000m for nominal power, 10% power degrading every 1000m (up to 3000m)

BTU Rating Online: 1186, Battery: 1608

Noise level <45 dB at 1 meter

Relative humidity 0-95% non-condensing

Temperature range 0° to 40°C (32° to 104°F)

Additional specifications

Special features

Gigabit Network Card (NETWORK-M2) included

Form factor

Rack/tower

Rack size

6U

Rack mounting kit

Yes

Efficiency

93%

Package contents

9PX5K 5 kVA UPS 9PXTFMR5 120V Stepdown Transformer Gigabit Network Card (Network-M2) 4-post rail kits (2x 9RK) User manual Quick start guide Tower pedestals Intelligent Power Software Suite CD RS-232 serial cable USB cable

Warranty and support

Standard factory warranty

3-YEAR FACTORY WARRANTY - 3 years - Parts, electronics and batteries coverage - Standard ground shipping - Technical support Extended service plans ADVANCED DEPOT EXCHANGE - 5-year depot repair: 9SW5Y-6000UC - Expedited parts coverage for 5 years - Parts, electronics and UPS batteries coverage - Next business day shipping - Technical support 5-YEAR ON-SITE PLAN: WFLN75XX-6009UC - On-site parts and labor coverage for years 5 - Parts, electronics and UPS batteries coverage

Cable gland for hardwire connection Phillips head screw driver

Internal bypass

Yes

- 24x7 on-site labor

coverage, next-day response

- coponoc
- Next-day shipping
- Technical support

Resources

Brochures

Eaton 9PX 5-11 kVA UPS brochure

9PX UPS bundles configuration overview

Drawings

9PXTFMR5 Pro-E drawing

Battery Integration System Pro-E drawing

9PX5K Pro-E drawing

Manuals and user guides

9PX UPS (5-6 kVA) user guide

9PX battery integration system user guide

9PX UPS maintenance bypass user guide

9PX PPDM and transformers user guide

Specifications and datasheets

9PX technical specifications: 5 and 6 kVA

Eaton Specification Sheet - 9PX5KTF5



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com © 2024 Eaton. All Right Reserved.

Eaton is a registered trademark.

Eaton.comAll other trademarks are© 2024 Eaton. All Rightsproperty of their respectiveReserved.owners.



Eaton.com/socialmedia