

Eaton 9SX1000

Catalog Number: 9SX1000

Eaton 9SX online, extended runtime UPS, 1000 VA, 900 W, 5-15P input, Outputs: (6) 5-15R, 9.9"Hx6.3"Wx15.1"D, 30.9 lb., network card optional



General specifications

Product Name	Catalog Number
Eaton 9SX UPS	9SX1000
UPC	Product Length/Depth
743172091239	15.1 in
Product Height	Product Width
9.9 in	6.3 in
Product Weight	Warranty
30.9 lb	3 year limited
Compliances	Certifications
FCC Compliant	cULus Listed
CE Marked	
ENERGY STAR certified	

Battery

Runtime graph

\$row.attributeValue.cdata

Battery management

ABM technology (3-stage charging extends battery service life by 50% and provides advance warning for battery replacement)

Battery replacement

Hot-swappable internal batteries and extended battery modules (EBMs)

Extended battery capability

Yes

Electrical output

Receptacle

(6) 5-15R

Topology

Online/Double-conversion

Wattage

900 W

VA rating

1000 VA

Output waveform

True sine wave

Voltage

120V

Output power factor

0.9

Output nominal voltage

120V default (100/110/120/125V)

Output frequency

50/60 Hz

Feed type

1

Electrical input

Input connection

5-15P

Input cord length

8 ft

Input frequency range

60 Hz: 50–70 Hz, 50 Hz: 40–60 Hz

Input power factor

>.99

Communications

Communication

- (1) MiniSlot
- (1) USB port
- (1) Serial RS-232 port
- (1) RPO/ROO/Signal input terminal
- (1) mini-terminal block for output relay

Expansion slots

- (1) Mini-Slot (MS) expansion port. Optional connectivity cards may be ordered separately.
 - Gigabit Web/SNMP card

part number: NETWORK-M2

- Modbus card part number: INDGW-M2
- Relay card part number: RELAY-MS

User interface

5-button graphical user interface

Potential free switch contact

Yes

Environmental

Temperature range

0° to 40°C (32° to 104°F)

Additional specifications

Special features

This product is designed with features typically required in commercial applications, including network connectivity and a metal case

Form factor

Tower

Construction type

Free standing model

Efficiency

90.81%

Package contents

9SX 1000 VA UPS
Quick start guide
RS-232 serial cable
USB cable

Internal bypass

Yes

Warranty and support

Standard factory warranty

3-YEAR FACTORY WARRANTY

- 3 years
- Parts, electronics and batteries coverage
- Standard ground shipping
- Technical support

Extended service plans

ADVANCED DEPOT EXCHANGE
-5-year depot repair:

Resources

Brochures

[Eaton 9SX UPS brochure](#)

Certification reports

[EC DoC Eaton 9SX](#)

Characteristic curve

[9SX1000 ups-battery-runtime graph](#)

Drawings

[9SX1000 UPS 3D technical drawing](#)

[Eaton 9SX UPS visio stencils](#)

[9SX1000 UPS 2D technical drawing](#)

Manuals and user guides

9SW5Y-1000UC

-Expedited parts coverage
for 5 years

-Parts, electronics and UPS
batteries coverage

-Next business day shipping

-Technical support

5-YEAR ON-SITE PLAN:

WFLN75XX-2509UC

- On-site parts and labor
coverage for years 5

- Parts, electronics and UPS
batteries coverage

- 24x7 on-site labor
coverage, next-day
response

- Next-day shipping

- Technical support

[Eaton 9SX UPS installation and user manual](#)

[Quick start guide for Eaton 9SX UPS 120V models](#)

[Specifications and datasheets](#)

[Eaton 9SX UPS technical specifications](#)

[Eaton Specification Sheet - 9SX1000](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights
Reserved.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



Eaton.com/socialmedia