

Eaton EMAU05-10

Catalog Number: EMAU05-10

Eaton Managed rack PDU, 2U, L5-30P input, 2.88 kW max, 120V, 24A, 10 ft cord, Single-phase, Outlets: (16) 5-20R

General specifications



Product Name	Catalog Number
Eaton Managed Rack PDU	EMAU05-10
UPC	Product Length/Depth
743172082688	19 in
Product Height	Product Width
5 in	3.4 in
Product Weight	Warranty
13 lb	3 year
Compliances	Certifications
Contact Manufacturer	UL Listed

Product specifications

Form factor

2U

Outlet control

Yes

Phase

Single-phase

Wattage

2.88 kW max

Amperage Rating

24A

Input voltage

120V

Input connection

L5-30P

Outlets

(16) 5-20R

Cord length

10 ft

Frequency rating

50-60 Hz

Operating Temperature

0° to 60°C (32° to 140°F)

Resources

Certification reports

[Eaton ePDU certificate of volatility](#)

[Eaton RoHS Declaration of Conformity: ePDU G3](#)

Drawings

[Eaton Advanced Monitored and Managed ePDU visio stencil](#)

[Eaton ePDU Managed EMAU05-10 technical drawing](#)

Manuals and user guides

[Eaton Double-wide G3 ePDU installation and connectivity quick start guide](#)

[Eaton ePDU G3 instruction set - system objects](#)

[Eaton ePDU G3 replace and configure eNMC module](#)

[Eaton ePDU G3 1U and 2U installation addendum](#)

[Eaton ePDU G3 operations manual](#)

Specifications and datasheets

[Eaton Specification Sheet - EMAU05-10](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia