

Eaton EMI310-10

Catalog Number: EMI310-10

Eaton Metered Input rack PDU, 0U, L21-30P input, 8.64 kW max, 120/208V, 24A, 10 ft cord, Three-phase, Outlets: (1) 5-20R, (30) C13 Outlet grip, (6) C19 Outlet grip

General specifications

Product Name	Catalog Number
Eaton metered input rack PDU	EMI310-10
UPC	Product Length/Depth
743172050410	2.05 in
Product Height	Product Width
66.5 in	2.1 in
Product Weight	Warranty
17.61 lb	3 year
Compliances	Certifications
TAA Compliant	UL Listed



Product specifications

Form factor

0U (Vertical)

Outlet control

No

Phase

Three-phase

Wattage

8.64 kW max

Amperage Rating

24A

Input voltage

120/208V

Input connection

L21-30P

Outlets

(1) 5-20R, (30) C13 Outlet grip, (6) C19 Outlet grip

Cord length

10 ft

Frequency rating

50-60 Hz

Ethernet interface

Yes

Serial interface

RS-232

Operating Temperature

0° to 60°C (32° to 140°F)

Resources

Certification reports

Eaton RoHS Declaration of Conformity: ePDU G3

Drawings

Eaton ePDU G3 Metered Input EMI310-10 technical drawing

Manuals and user guides

Eaton ePDU G3 instruction set - system objects

Eaton ePDU G3 EMP installation and connection quick start guide

Eaton ePDU G3 installation and connectivity quick start guide

Eaton ePDU G3 operations manual

Service and troubleshooting

EMI310-10 eNMC replacement configuration file

Specifications and datasheets

Eaton Specification Sheet - EMI310-10



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



Eaton.com/socialmedia