FLIR K33

P/N: 72203-0411

Copyright

© 2022, FLIR Systems, Inc.

All rights reserved worldwide. Names and marks appearing herein are either registered trademarks or trademarks of FLIR Systems and/or its subsidiaries. All other trademarks, trade names or company names referenced herein are used for identification only and are the property of their respective owners.

Document identity

Publ. No.: 72203-0411
Commit: 87197
Language:
Modified: 2022-09-21
Formatted: 2022-10-11

Website

http://www.flir.com

Customer support

http://support.flir.com

Disclaimer

Specifications subject to change without further notice. Camera models and accessories subject to regional market considerations. License procedures may apply. Products described herein may be subject to US Export Regulations. Please refer to exportquestions@flir.com with any questions.



General description
The FLIR K33 is a robust and reliable infrared camera designed to perform under extremely severe conditions. The FLIR K33 has an intuitive interface with a design that makes it easy to control even with a gloved hand. The crisp and clear image helps you to navigate through smoke and to make quick and accurate decisions.
Benefits:
• Robust and reliable: The FLIR K33 is designed to meet tough operating conditions. It can withstand a drop from 2 m (6.5 ft.) onto a concrete floor, is water resistant to IP67, and is fully operational up to +85°C (+185°F), or +260°C (+500°F) for 5 min. • Clear and crisp thermal images: The maintenance-free uncooled microbolometer sensor produces clear and detail-rich images of 240 × 180 pixels which have been further improved with FSX, a digital image processing enhancement technique. Thermal images are presented on a large, bright 4″ display, helping you to navigate and to make quick and accurate decisions. • Easy-to-use—also in a gloved firefighter's hand: An intuitive and simple user interface allows you to focus on the job. The FLIR K33 can be controlled by just one large button on top of the unit. Ideal for a gloved firefighter's hand.

Imaging and optical data	
IR resolution	240 × 180 pixels
Thermal sensitivity/NETD	< 40 mK @ +30°C (+86°F)
Field of view (FOV)	51° × 38°
Depth of field	0.84 m to infinity (33 in. to infinity)
Focal length	9 mm (0.35 in.)
Spatial resolution (IFOV)	3.6 mrad
F-number	1.25
Image frequency	60 Hz
Focus	Fixed

P/N: 72203-0411
© 2022, FLIR Systems, Inc.
#72203-0411; r. 87197;

Detector data	
Detector type	Focal plane array (FPA), uncooled microbolometer
Spectral range	7.5–13 µm
Pitch	25 µm

Image presentation	
Display	4 in. LCD, 320 × 240 pixels, backlit
Auto range	Yes, selectable on/off using FLIR K-series camera configurator
Contrast optimization	Digital image enhancement using FSX

Image presentation modes	
Image modes	Basic mode

Measurement	
Object temperature range	• –20°C to +150°C (–4°F to +302°F) • 0°C to +650°C (+32°F to +1202°F)
Accuracy	±4°C (±7.2°F) or ±4% of reading, for ambient temperature 10°C to 35°C (+50°F to 95°F)

Measurement analysis	
Spotmeter	1
Isotherm	Yes

Set-up	
Set-up commands	Local adaptation of units, date and time formats
Languages	English

Video streaming	
Non-radiometric IR video streaming	Uncompressed colorized video using USB

USB	
USB	USB Mini-B

Data communication interfaces	
Interfaces	• Update from PC devices • Data transfer to and from PC

Power system	
Battery type	Li Ion
Battery voltage	3.6 V
Battery capacity	4.4 Ah, at +20°C to +25°C (+68°F to +77°F)
Battery operating time	Approx. 4 hours at +25°C (+77°F) ambient temperature and typical use
Charging system	• Battery is charged inside the camera • 2-bay charger • Optional In-truck charger
Charging time	2 h to 85% capacity, charging status indicated by LEDs

P/N: 72203-0411
© 2022, FLIR Systems, Inc.
#72203-0411; r. 87197;

Power system	
Charging temperature	0°C to +45°C (+32°F to +113°F)
Power management	Automatic shutdown and sleep mode
Start-up time from sleep mode	< 4 s.
Start-up time	< 17 s. (IR image, no GUI)
Battery documents	For documents like MSDS and UN38.3 test reports/summaries, see: https://support.flir.com/resources/msds

Environmental data	
Operating temperature range	• –20°C to +85°C (–4°F to +185°F) • +150°C (+302°F): 15 min. • +260°C (+500°F): 5 min.
Storage temperature range	–40°C to +85°C (–40°F to +185°F)
Humidity (operating and storage)	IEC 60068-2-30/24 h 95% relative humidity +25° C to +40°C (+77°F to +104°F) / 2 cycles
Relative humidity	95% relative humidity +25°C to +40°C (+77°F to +104°F) non-condensing
EMC	• EN 61000-6-2:2005 (Immunity) • EN 61000-6-3: 2011 (Emission) • FCC 47 CFR Part 15 B (Emission)
Magnetic fields	EN 61 000-4-8, Test level 5 for continuous field (severe industrial environment)
Encapsulation	IP 67 (IEC 60529)
Shock	25 g (IEC 60068-2-27)
Vibration	2 g (IEC 60068-2-6)
Drop	2 m (6.6 ft.) on concrete floor (IEC 60068-2-31)
Safety (power supply)	CE/EN/UL/CSA/PSE 60950-1
Declaration of conformity	See: https://support.flir.com/resources/DoC

Physical data	
Camera weight, incl. battery	1.1 ±0.05 kg (2.4 ±0.1 lb.)
Battery weight	0.152 kg (0.3 lb.)
Camera size (L × W × H)	120 × 125 × 280 mm (4.7 × 4.9 × 11 in.)
Tripod mounting	UNC ¼"-20 (adapter needed)
Material	• PPSU • Silicon rubber • Aluminium, cast • Flame-resistant magnesium alloy


P/N: 72203-0411
© 2022, FLIR Systems, Inc.
#72203-0411; r. 87197;

Shipping information	
List of contents	• Infrared camera • Battery (2 ea.) • Battery charger • Carabiner strap • Hard transport case • Power supply • Printed documentation • Retractable lanyard, 16 N (58 oz) • USB cable
Packaging, weight	5.7 kg (12.6 lb.)
Packaging, size	500 × 190 × 370 mm (19.7 × 7.5 × 14.6 in.)
EAN-13	7332558011515
UPC-12	845188012465
Country of origin	Estonia

Supplies & accessories:

- 1910423; USB cable Std A <-> Mini-B
- T198509; Cigarette lighter adapter kit, 12 VDC, 1.2 m/3.9 ft.
- T198125; Battery charger, incl. power supply with multi plugs (Exx, Kxx)
- T127724ACC; Neck strap
- T198416ACC; Lanyard strap
- T198457ACC; Tripod Adapter, Kxx
- T198441ACC; Transport case Kxx
- T198322ACC; In-truck charger
- T199368ACC; Battery Li-ion 3.6 V, 4.4 Ah, 16 Wh
- T129915ACC; Carabiner strap
- T130980ACC; Retractable lanyard, 16 N (58 oz)
- T300466ACC; Battery locking mechanism replacement kit

This document must not be communicated or copied completely or in part, without our permission. Any infringement will lead to legal proceedings.
FLIR SYSTEMS AB



Konstr/Drawn A. LUND	Datum/Date 2016-03-23	Kontr/Check	Material	
Ändrad av/Modified by A. LUND	Ändrad/Modified 2016-03-29	Ytjämnhet/Roughness Ra µm	Ytbehandling/Surface treatment	

Där ej annat anges/Unless otherwise stated
Gen tol ISO 2768-mK
Utdrag ur/Excerpt from ISO 2768-m

0,5-6	±0,1	Hålkälsradier
(6)-30	±0,2	Fillet radii
(30)-120	±0,3	
(120)-400	±0,5	Kanter brutna
(400)-1000	±0,8	Edges broken


Benämning/Denomination


Basic dimension drawing

Skala/Scale 1:2		Blad/Sheet 1(2)
ArtNo.		Size A3
Ritn nr/Drawing No Kx3		Rev

Denna handling får ej delges annan, kopieras i sin helhet eller delar utan vårt medgivande och innehållet får ej obevakat obevisas med stöd av gällande lag.
FLIR SYSTEMS AB

This document must not be communicated or copied completely or in part, without our permission. Any infringement will lead to legal proceedings.
FLIR SYSTEMS AB





Konstr/Drawn: A. LUND	Datum/Date: 2016-03-23	Kontr/Check:	Material: -
Ändrad av/Modified by: A. LUND	Ändrad/Modified: 2016-03-29	Ytjämnhet/Roughness: Ra µm	Ytbehandling/Surface treatment

Där ej annat anges/Unless otherwise stated
Gen tol ISO 2768-mK
Utdrag ur/Excerpt from ISO 2768-m


0,5-6	±0,1	Hålkälsradier
(6)-30	±0,2	Fillet radii
(30)-120	±0,3	
(120)-400	±0,5	Kanter brutna
(400)-1000	±0,8	Edges broken


Benämning/Denomination: Basic dimension drawing

Skala/Scale: 1:2		Blad/Sheet: 2(2)
ArtNo.		Size: A3
Ritn nr/Drawing No: Kx3		Rev

Denna handling får ej delges annan, kopieras i sin helhet eller delar utan vårt medgivande. Överträdelse hänskjuts till tvist avgörande av gällande lag.
FLIR SYSTEMS AB

This document must not be communicated or copied completely or in part, without our permission. Any infringement will lead to legal proceedings.
FLIR SYSTEMS AB





-

Konstr/Drawn	Datum/Date	Kontr/Check	Material
P. MARCUS	2013-04-08	MABR	
Ändrad av/Modified by	Ändrad/Modified	Ytjämnhet/Roughness	Ytbehandling/Surface treatment
P. MARCUS	2013-04-08	Ra µm	

Där ej annat anges/Unless otherwise stated
Gen tol ISO 2768-mK
Utdrag ur/Excerpt from ISO 2768-m

0,5-6	±0,1	Hålkälsradier
(6)-30	±0,2	Fillet radii
(30)-120	±0,3	
(120)-400	±0,5	Kanter brutna
(400)-1000	±0,8	Edges broken

Benämning/Denomination

Basic dimensions
In-truck charger

Skala/Scale	Blad/Sheet
1:5	1(1)
Art.No.	Size
	A4
Ritn nr/Drawing No	Rev
T127865	A

Denna handling får ej delges annan, kopieras i sin helhet eller delar utan vårt medgivande. Överträdelse härav beivras med stöd av gällande lag.
FLIR SYSTEMS AB