


AC2380



AS-Interface illuminated pushbutton module

AS-i Module 2BI 2LO WT/BL IP69K



Application

Application field installation; sanitary and wet areas in the food industry

Electrical data

Operating voltage [V] 26.5...31.6 DC

Max. current consumption [mA] from AS-i 80

Inputs

Sensor supply of the inputs AS-i

Outputs

Electrical design AS-i

Operating conditions

Ambient temperature [°C] -25...70

Storage temperature [°C] -40...80

Protection IP 67; IP 68; IP 69K

Tests / approvals

EMC EN 61000-6-2

EN 62026-2

AS-i classification

AS-i version 2.11; 3.0

AC2380



AS-Interface illuminated pushbutton module

AS-i Module 2BI 2LO WT/BL IP69K

Extended addressing mode	yes				
AS-i master profile	M2; M3; M4				
AS-i profile	S-B.A.E				
AS-i I/O configuration [hex]	B				
AS-i ID code [hex]	A.E				
AS-i certificate	135301				
Data bits	Data bit	D0	D1	D2	D3
	LED 1 blue	DO-0	-	-	-
	LED 2 white	-	DO-1	-	-
	pushbuttons 1	-	-	DI-2 (NO)	-
	pushbuttons 2	-	-	-	DI-3 (NO)

Mechanical data

Weight [g]	275.6
Housing	rectangular
Type of mounting	screw mounting
Dimensions [mm]	118 x 46.5 x 50
Material	housing: stainless steel

Displays / operating elements

Display	Power	LED, green
	errors	LED, red
Operating elements	2	freely programmable backlit function keys

Electrical connection

Module connection	M12
-------------------	-----

Remarks

Remarks	The pushbutton modules (RAFI type RAFIX22) offer protection against accidental contact.
Pack quantity	1 pcs.

Electrical connection

	
1	AS-i +
3	AS-i -