


AC2910



AS-Interface ProcessLine module

ProcessLine 8DI IP69K



Application

Application	sanitary and wet areas in the food industry
-------------	---

Electrical data

Operating voltage	[V]	26.5...31.6 DC
Max. current consumption from AS-i	[mA]	500

Inputs / outputs

Number of inputs and outputs	Number of digital inputs: 8
------------------------------	-----------------------------

Inputs

Number of digital inputs		8; (2 x Slave)
Input circuit of digital inputs		PNP; (type 2 according to IEC 61131-2)
Sensor supply of the inputs		AS-i
Voltage supply	[V]	18...30; (DC)
Max. total current rating of inputs	[mA]	400
Input current High	[mA]	6...10
Input current low	[mA]	0...2
Switching level high	[V]	> 11
Digital inputs protected against short circuits		yes

Operating conditions

Ambient temperature	[°C]	-5...70
Max. relative air humidity	[%]	90; (linearly decreasing to 50 % (40 °C) non condensing)
Max. height above sea level	[m]	2000
Protection		IP 68; IP 69K
Degree of soiling		2

Tests / approvals

EMC	EN 62026-2	
	EN 61000-6-2	



AS-Interface ProcessLine module

ProcessLine 8DI IP69K

MTTF	[years]	212			
AS-i classification					
AS-i version		2.1			
Extended addressing mode		yes			
AS-i master profile		M2; M3; M4			
AS-i profile		S-0.A.E			
AS-i I/O configuration	[hex]	0			
AS-i ID code	[hex]	A.E			
AS-i certificate		88901			
Data bits	Data bit	D0	D1	D2	D3
	Input	1	2	3	4
	Socket	I-1/2	I-1/2 / I-2	I-3/4	I-3/4 / I-4
	Pin	4	2 4	4	2 4
Mechanical data					
Weight	[g]	644			
Housing		tubular			
Type of mounting		Mounting base			
Dimensions	[mm]	Ø 137.3 / L = 80			
Material		threaded bush: stainless steel (1.4404 / 316L); LED-Fenster: PC; O-ring: EPDM; Protective cap: PP			
Displays / operating elements					
Display	Power	LED, green			
	errors	LED, red			
	Function	LED, yellow			
Electrical connection					
Module connection		M12			
Accessories					
Items supplied		Protective cap: M12, E70297			
Accessories (optional)		Torque wrench:, E70390			
		Flat cable insulation displacement connector:, E70454			
Remarks					
Remarks		Inputs and outputs must be electrically isolated.			
		Do not connect any of the following points to an external potential:			
		I-, I+, I-1/2, I-2, I-3/4, I-4			
		The connections are electrically connected with the AS-i cable.			
		Default setting of the ID1 codes: slave 1=1 / slave 2=2			
		The round cable connected to AS-i should not be longer than 2m.			
Pack quantity		1 pcs.			




AS-Interface ProcessLine module

ProcessLine 8DI IP69K

Electrical connection - AS-i


Connector: M12; coding: A; Tightening torque: 1.2...1.4 Nm




1	AS-i+
2	n.c.
3	AS-i -
4	n.c.
5	functional earth FE

Electrical connection - Inputs

Connection



Connector: M12; coding: A; Tightening torque: 1.2...1.4 Nm



1	Sensor supply L+
3	Sensor supply L-
5	functional earth