


AC514A



AS-Interface ClassicLine module with quick mounting technology

ClassicL 2DO-Y 2DI-Y II 3D



Application	
Design	housing for DIN rail mounting
Application	AS-i ATEX module
Electrical data	
Operating voltage [V]	26.5...31.6 DC
Max. current consumption from AS-i [mA]	150
Max. current load total [A]	2
Integrated watchdog	yes
Inputs / outputs	
Number of inputs and outputs	Number of digital inputs: 2; Number of digital outputs: 2
Inputs	
Number of digital inputs	2
Input circuit of digital inputs	PNP
Sensor supply of the inputs	AS-i
Voltage supply [V]	18...30; (via flat cable)
Max. total current rating of inputs [mA]	100
Input current High [mA]	6...10
Input current low [mA]	0...2
Switching level high [V]	> 11
Digital inputs protected against short circuits	yes

AC514A



AS-Interface ClassicLine module with quick mounting technology

ClassicL 2DO-Y 2DI-Y II 3D

Outputs					
Number of digital outputs	2				
Circuit	PNP				
Voltage range DC [V]	15...30; (to PELV; via flat cable)				
Max. current load per output [mA]	1000; (utilization category DC-13 (control of electromagnets): 20 W (IEC 60947-5-1))				
Short-circuit proof	yes				
Electrically separated	yes				
Operating conditions					
Ambient temperature [°C]	-10...50				
Protection	IP 50				
Tests / approvals					
ATEX marking	 II 3D Ex tc IIIB T80°C Dc X IP50				
EMC	EN 50295				
	IEC 61000-6-2				
MTTF [years]	192				
AS-i classification					
AS-i version	2.11; 3.0				
AS-i addressing	Addressing socket				
Extended addressing mode	yes				
AS-i master profile	M2; M3; M4				
AS-i profile	S-B.A.E				
AS-i I/O configuration [hex]	B				
AS-i ID code [hex]	A.E				
AS-i certificate pending	yes				
Data bits	Data bit	D0	D1	D2	D3
	Input	-	-	3	4
	Socket	-	-	I-3/4	I-3/4 I-4
	Pin	-	-	4	2 4
	Output	1	2	-	-
	Socket	O-1/2	O-1/2 / O-2	-	-
	Pin	4	2 4	-	-
Mechanical data					
Weight [g]	239.5				
Housing	rectangular				
Type of mounting	AS-i flat cable connection; Mounting on DIN rail; (TH35 (EN 60715))				
Dimensions [mm]	103 x 45 x 44.7				
Material	PA; Piercing contacts: CuSn6 nickel-plated and tin-plated				
Displays / operating elements					
Display	Power	LED, green			
	errors	LED, red			
	Function	LED, yellow			
Electrical connection					
Module connection	Flat cable				

AC514A




AS-Interface ClassicLine module with quick mounting technology

ClassicL 2DO-Y 2DI-Y II 3D


Accessories	
Items supplied	lower part
Accessories (optional)	Protective cap: M12, E73004
	impact protection housing:, E7000A
Remarks	
Remarks	Mechanical protection has to be implemented.
	Otherwise the unit must be installed together with the impact protection housing (E7000A).
	Do not connect any of the following points to an external potential:
	I-, I+, I-3/4, I-4
	The connections are electrically connected with the AS-i cable.
	Inputs and outputs must be electrically isolated.
Pack quantity	1 pcs.

Electrical connection

quick mounting technology for AS-i flat cable: ; three selectable directions



Connection






AS-Interface ClassicLine module with quick mounting technology

ClassicL 2DO-Y 2DI-Y II 3D

Electrical connection - Inputs

Connection




Connector: M12

Inputs	
Socket I-3/4	
1	Sensor supply L+
2	Data input 4
3	voltage supply L-
4	Data input 3
5	not used
Socket I-4	
1	Sensor supply L+
2	not used
3	Sensor supply L-
4	Data input 4
5	not used



Electrical connection - Outputs

Connection



Connector: M12

Outputs	
Socket O-1/2	
1	not used
2	Switching output 2
3	External voltage AUX -
4	Switching output 1
5	not used
Socket O-2	
1	not used
2	not used
3	External voltage AUX -
4	Switching output 2
5	not used