


AC5249



AS-Interface Airbox with quick mounting technology

AirBox 5/2 4DI-Y IP67 AUX



Application

Design	housing for DIN rail mounting
Application	field installation
Medium temperature [°C]	-10...50

Electrical data

Operating voltage [V]	26.5...31.6 DC
Max. current consumption from AS-i [mA]	300
Additional voltage supply [V]	18...30 DC; (to PELV)
Additional voltage supply	required
Max. current consumption from additional supply [mA]	10
Integrated watchdog	yes



AS-Interface Airbox with quick mounting technology

AirBox 5/2 4DI-Y IP67 AUX

Inputs / outputs						
Number of inputs and outputs		Number of digital inputs: 4; Number of pneumatic outputs: 1				
Inputs						
Number of digital inputs		4				
Input circuit of digital inputs		PNP				
Sensor supply of the inputs		AS-i				
Voltage supply [V]		20...30; (via flat cable)				
Max. total current rating of inputs [mA]		200				
Input current High [mA]		6...10				
Input current low [mA]		0...2				
Switching level high [V]		> 11				
Digital inputs protected against short circuits		yes				
Outputs						
Number of pneumatic outputs		1; (pneumatic NO/NC selectable output ; monostable; supply: external 24 V power supply)				
Actuator supply outputs		AUX				
Operating conditions						
Ambient temperature [°C]		-10...55				
Protection		IP 65; IP 67				
Tests / approvals						
EMC		EN 50295				
		IEC 61000-6-2				
MTTF [years]		257				
AS-i classification						
AS-i version		2.11; 3.0				
AS-i addressing		Addressing socket				
Extended addressing mode		yes				
AS-i master profile		M2; M3; M4				
AS-i profile		S-7.A.E				
AS-i I/O configuration [hex]		7				
AS-i ID code [hex]		A.E				
Data bits		Data bit	D0	D1	D2	D3
		Input	1	2	3	4
		Socket	I-1/2	I-1/2 I-2	I-3/4	I-3/4 I-4
		Pin	4	2 4	4	2 4
		pneumatic output	4	-	-	-
Mechanical data						
Weight [g]		369				
Housing		rectangular				
Type of mounting		quick mounting; AS-i flat cable connection; Mounting on DIN rail; (TH35 (EN 60715))				
Dimensions [mm]		108 x 85 x 50				
Material		PA; POM; Piercing contacts: CuSn6 nickel-plated and tin-plated				
Pneumatic system		1 x 5/2-way slide valve (free from overlapping)				
Operating pressure range		3...8 bar	0.3...0.8 MPa		43.5...116 psi	

AC5249



AS-Interface Airbox with quick mounting technology

AirBox 5/2 4DI-Y IP67 AUX

Air flow at 6/5 bar	[l/min]	500
Permissible compressed air	non-lubricated compressed air class 6-3-1; lubricated compressed air class 6-3-4	
Manual override	pressing/releasing or pressing/turning/locking	
Tube fittings	8 mm	
Exhaust	exhaust can be discharged through tube connection	

Displays / operating elements

Display	Power	LED, green
	errors	LED, red
	Function	LED, yellow

Electrical connection

Module connection	Flat cable
-------------------	------------

Accessories

Items supplied	lower part
Accessories (optional)	Mounting plate:, E74999
	Module lower part:, E75000
	Protective cap: M12, E73004
	sealing plug:, E75231
	Silencer:, E75232
	Push-in L-fitting:, E75228
	Push-in T-fitting:, E75227

Remarks

Remarks	If not pneumatically operated, E75231 sealing plug must be inserted.
	Avoid ingress of dirt and dust.
	Do not connect any of the following points to an external potential:
	L-, L+, I-1, I-2, I-3, I-4
	The connections are electrically connected with the AS-i cable.
	Please see the notes on compressed air and EMC/ESD under "Downloads"
Pack quantity	1 pcs.




AS-Interface Airbox with quick mounting technology

AirBox 5/2 4DI-Y IP67 AUX

Electrical connection

quick mounting technology for AS-i flat cable: ; three selectable directions

Connection



Connector: M12

Inputs	
Socket I-1/2	
1	Sensor supply L+
2	Data input 2
3	Sensor supply L-
4	Data input 1
5	not used
Socket I-2	
1	Sensor supply L+
2	not used
3	Sensor supply L-
4	Data input 2
5	not used
Socket I-3/4	
1	voltage supply L+
2	Data input 4
3	Sensor supply L-
4	Data input 3
5	not used
Socket I-4	
1	Sensor supply L+
2	not used
3	Sensor supply L-
4	Data input 4
5	not used




AS-Interface Airbox with quick mounting technology

AirBox 5/2 4DI-Y IP67 AUX

Diagrams and graphs

Pneumatic symbol



1 x 5/2-way slide valve (free from overlapping) monostable