


DP3613



Relay adapter

RELAIS ADAPTER/2xNC/IP69K



Product characteristics	
Output function	normally closed
Dimensions [mm]	63 x 30 x 23
Electrical data	
Operating voltage [V]	18...30 DC; ((in wet environments: 18...28 V) ; to SELV/PELV)
Nominal voltage DC [V]	24
Current consumption [mA]	< 10
Nass	
Operating voltage [V]	18...28 DC
Inputs / outputs	
Number of inputs and outputs	Number of digital inputs: 2; Number of relay outputs: 2
Inputs	
Number of digital inputs	2; (type 3 (IEC 61131-2))
Outputs	
Voltage range DC [V]	0...32; (to SELV/PELV)
Voltage range AC [V]	0...20; ((in wet environments: 0...16 V); to SELV/PELV)
Output function	normally closed
Max. current load per output [mA]	1000; (Socket Pin 1: 2000 mA)
Number of relay outputs	2
Switching frequency AC [Hz]	1
Switching frequency DC [Hz]	1
Notes on switching frequency [Hz]	no capacitive loads
Operating conditions	
Ambient temperature [°C]	-25...60
Note on ambient temperature	2000 m: -25...60 °C
	3000 m: -25...55 °C
	4000 m: -25...52 °C
Storage temperature [°C]	-25...70

DP3613



Relay adapter

RELAIS ADAPTER/2xNC/IP69K

Max. relative air humidity	[%]	90; (linearly decreasing to 50 % (40 °C) non condensing)	
Max. height above sea level	[m]	4000	
Protection		IP 67; IP 69K	
Degree of soiling		2; (before installation and when the device is replaced)	
Chemical media		DIN EN ISO 175, Ecolab test method 40-1	
		the following media were tested for 28 days at constant room temperature using the dipping test method	P3-topax 66
			P3-topax 990
			Topactive 200
			Topactive 500
			Topactive OKTO

Tests / approvals

MTTF	[years]	942	
UL approval		Ta	max. 55 °C
		File number UL	E205959

Mechanical data


Weight	[g]	75.3	
Weight (without accessories and packaging)	[g]	35	
Dimensions	[mm]	63 x 30 x 23	
Material		housing: PA; knurled nut: stainless steel (1.4404 / 316L)	
Sealing material		FKM	

Remarks

Remarks	Further information is available in the manual. the device complies with overvoltage category II		
Pack quantity	1 pcs.		

Electrical connection - plug

Connector: 1 x M12, straight; coding: A; sealing: FKM



- 1: L+
- 2: IN1 DI
- 3: L-
- 4: IN2 DI

DP3613




Relay adapter

RELAIS ADAPTER/2xNC/IP69K

Electrical connection - Socket

Connector: 1 x M12, straight; coding: A; sealing: FKM



1: L1 / L+	(AC/DC)
2: OUT1	NC
3: n.c.	
4: OUT2	NC
5: n.c.	