


# DTE904



## Compact RFID device

DTRUHFA HLRWENUS04



Application	
Radio approval for	USA; Canada; Mexico
Electrical data	
Operating voltage [V]	19.2...28.8 DC
Current consumption [mA]	500
Power consumption [W]	8.6
Protection class	III
Operating frequency [MHz]	902...928
RFID standard	EPC Class1 GEN2/ISO 18000-63
Transmission power EIRP [mW]	200; (maximum: 250 mW)
Inputs / outputs	
Number of inputs and outputs	Number of digital outputs: 2
Outputs	
Total number of outputs	2
Electrical design	push-pull
Number of digital outputs	2
Max. voltage drop switching output DC [V]	2
Max. current load per output [mA]	100; (max.)
Short-circuit protection	yes
Overload protection	yes
Interfaces	
Communication interface	Ethernet
Ethernet - TCP/IP	
Protocol	TCP/IP
Factory settings	IP address: 192.168.0.79 subnet mask: 255.255.255.0 gateway IP address: 192.168.0.100
Usage type	Parameter setting; Data transmission

# DTE904



## Compact RFID device

DTRUHFA HLRWENUS04

Operating conditions	
Ambient temperature [°C]	-20...55
Note on ambient temperature	with mounting plate and cooling element: -20...60 °C
Storage temperature [°C]	-25...80
Protection	IP 67

Tests / approvals		
Shock resistance	IEC 60028-2-27	40 g (6 ms) / bump
		50 g (11 ms) / single shock
Vibration resistance	EN 60068-2-6	2 g (10...150 Hz)

Mechanical data	
Weight [g]	695
Dimensions [mm]	113 x 118.6 x 50
Material	lower part: aluminum; Upper part: PBT / PC; plug: stainless steel

Displays / operating elements		
Display	voltage supply	1 x LED, green
	LED display	4 x LED, yellow signal strength ID tag
	status	2 x LED, green/red fieldbus interface
	status	2 x LED, green/yellow Ethernet

Remarks	
Pack quantity	1 pcs.

### Electrical connection - Ethernet

Connector: 2 x M12; coding: D




### ETH1 / ETH2

1	TD+
2	RD+
3	TD-
4	RD-

### Electrical connection - voltage supply

Connector: 1 x M12; coding: A



# DTE904



## Compact RFID device

DTRUHFA HLRWENUS04

PWR	
1	L+
2	digital input/output 2
3	L-
4	digital input/output 1
5	not used