


DV1150



LED strip RGBW

LED-Strip-RGBW-transp-62,5mm-cl

IO-Link-capable with DP1615



Application

Special feature	Halogen-free; Gold-plated contacts; Drag chain suitability
Application	signalling machine conditions

Electrical data

Operating voltage	[V]	21.6...26.4 DC
Nominal voltage DC	[V]	24; (to SELV/PELV)
Max. current consumption	[mA]	50; (red: 10; green: 10; blue: 10; white: 20)
Colour temperature	[K]	7500
Luminous flux	[lm]	red: 8; green: 22; blue: 6; white: 48
Typ. lifetime	[h]	60000

Inputs

Input circuit of digital inputs	24 V PNP
---------------------------------	----------

Operating conditions

Ambient temperature	[°C]	-20...45
Storage temperature	[°C]	-25...65
Max. relative air humidity	[%]	90
Max. height above sea level	[m]	4000
Protection		IP 68
Pollution degree		2

Tests / approvals

Approval	EN 62471; IEC 62031
Note on approval	EN 62471: risk group 0

Mechanical data

Weight	[g]	208
Dimensions	[mm]	90.5 x 14 x 8.4
Materials		housing: TPU
Sealing material		FKM
Drag chain suitability		yes

DV1150



LED strip RGBW

LED-Strip-RGBW-transp-62,5mm-cl

Drag chain suitability	bending radius for flexible use	min. 10 x cable diameter
	travel speed	max. 3.3 m/s for a horizontal travel length of 5 m and max. acceleration of 5 m/s ²
	bending cycles	> 1 Mio.
	torsional strain	± 180 °/m

Displays / operating elements

Display	signalling machine conditions	LED, multi-colour RGB
	mounting light	LED, white


Remarks

Notes	IO-Link-capable with DP1615
Pack quantity	1 pcs.

Electrical connection

Cable: 0.3 m, PUR, Halogen-free, black, Ø 4.3 mm; 5 x 0.34 mm² (42 x Ø 0.1 mm)


Connector: 1 x M12, straight; coding: A; Contacts: 5, gold-plated; Moulded body: TPU, orange; Locking: brass, nickel-plated; Sealing: FKM; Tightening torque: 0.6...1.5 Nm



1	L+	(red)
2	L+	(green)
3	L-	
4	L+	(white)
5	L+	(blue)

Diagrams and graphs

wavelength of the red light spectrum




DV1150




LED strip RGBW

LED-Strip-RGBW-transp-62,5mm-cl

wavelength of the green light spectrum



wavelength of the blue light spectrum




DV1150



LED strip RGBW

LED-Strip-RGBW-transp-62,5mm-cl

wavelength of the white light
spectrum



- 1 brightness
- 2 Wave length