


DV1530



5-segment signal lamp

LED-Tower-5/Std/Buzzer



1 buzzer



Application	
Application	signaling machine conditions
Electrical data	
Operating voltage [V]	18...30 DC; (to SELV/PELV)
Nominal voltage DC [V]	24
Current consumption [mA]	< 200
Inputs / outputs	
Number of inputs and outputs	Number of digital inputs: 6
Inputs	
Number of digital inputs	6
Input current High [mA]	6

DV1530



5-segment signal lamp

LED-Tower-5/Std/Buzzer

Interfaces		
Communication interface	IO-Link	
Transmission type	COM2 (38,4 kBaud)	
IO-Link revision	1.1	
SDCI standard	IEC 61131-9	
SIO mode	yes	
Required master port class	A	
Min. process cycle time [ms]	8	
Supported DeviceIDs	Type of operation	DeviceID
	Default	850
	Status B	1076
Operating conditions		
Ambient temperature [°C]	-25...50	
Storage temperature [°C]	-40...75	
Max. relative air humidity [%]	90	
Air pressure [kPa]	< 106	
Max. height above sea level [m]	2000	
Protection	IP 54	
Tests / approvals		
MTTF [years]	76	
Mechanical data		
Weight [g]	567	
Dimensions [mm]	Ø 70 / L = 284	
Material	housing: ABS; lens: PC	
Displays / operating elements		
Display	status	1 x LED, green
	LED segment	5 x 4 LED
Acoustic signal	buzzer	
Max. sound pressure [dB]	85	
Accessories		
Accessories (optional)	mounting base, E89060	
	wall bracket, E89061	
	Mounting adapter, E89063	
	bracket with lateral cable entry, E89064	
	mounting tube, E89065	
	mounting tube, E89066	
	mounting tube, E89067	
Remarks		
Remarks	Further information is available in the manual.	
Pack quantity	1 pcs.	

DV1530




5-segment signal lamp

LED-Tower-5/Std/Buzzer

Electrical connection - plug

Connector: M12; coding: A



Connection

1	Digital input LED segment 5
2	buzzer
3	Digital input LED segment 3
4	Digital input LED segment 2
5	voltage supply
6	Digital input LED segment 1
7	Digital input LED segment 4
8	IO-Link (C/Q)

DV1530




5-segment signal lamp

LED-Tower-5/Std/Buzzer

Diagrams and graphs

Installation




DV1530

5-segment signal lamp

LED-Tower-5/Std/Buzzer



Installation



- 1 mounting on a horizontal surface
- 2 mounting on a vertical surface


DV1530



5-segment signal lamp

LED-Tower-5/Std/Buzzer

base mounting



1 E89060 not supplied

2 E89065, E89066, E89067 not supplied


DV1530



5-segment signal lamp

LED-Tower-5/Std/Buzzer

wall mounting



- 1 E89060 not supplied
- 2 E89065, E89066, E89067 not supplied
- 3 E89061 not supplied