


# E12543



## Female cordset

ADOGS030PLS0001H03



Application		
System	Free from silicone; Halogen-free; Drag chain suitability	
Application	Industrial applications; Oils and coolants; Use in mobile and harsh applications	
Free from silicone	yes	
Electrical data		
Operating voltage [V]	8...32 DC	
Protection class	III	
Max. current load total [A]	4	
Operating conditions		
Ambient temperature [°C]	-40...85	
Ambient temperature (moving) [°C]	-20...85	
Protection	IP 67; (mating connector plugged in)	
Mechanical data		
Weight [g]	64.2	
Material	PA	
Molded-body material	PA	
Drag chain suitability	yes	
Drag chain suitability	Bending radius for flexible applications	min. 10 x cable diameter
	Travel speed	max. 3.3 m/s for a horizontal travel length of 5 m and max. acceleration of 5 m/s <sup>2</sup>
	Bending cycles	> 5 Mio.
	Torsional strain	± 180 °/m

# E12543



## Female cordset

ADOGS030PLS0001H03

### Remarks

Pack quantity 1 pcs.

### Electrical connection


Cable: 1 m, PUR, Halogen-free, black, Ø 5.4 mm; 3 x 0.50 mm<sup>2</sup> (28 x Ø 0.15 mm )

### Electrical connection - Socket

Connector: 1 x DEUTSCH connector, straight; Moulded body: PA; Contacts: nickel-plated



### Connection



BK = Core colors :  
black  
BN = brown  
RD = red