


E21316



Fiber optic diffuse reflection sensor

FT-11-EPV-O6/FHx1/2m



- 1 hexagon socket 3 mm
- 2 drill hole for mounting tools

Application	
Function principle	Diffuse reflection sensor
Application	For use in industrial environments
Monitoring range	
Range with fiber optic amplifier type	OBF; OCF; OO50
OBF	
Range of fiber optics [mm]	70
OCF (High Power)	
Range of fiber optics [mm]	980

E21316



Fiber optic diffuse reflection sensor

FT-11-EPV-O6/FHx1/2m

OO50		
Range of fiber optics	[mm]	150
Operating conditions		
Ambient temperature	[°C]	-40...70
Mechanical data		
Weight	[g]	50
Version of sensing head		angled
Sensing head thread		M6
Sensing head length	[mm]	17.5
Total length	[mm]	2000
Min. bending radius	[mm]	2
Fiber arrangement		⊙
Core diameter	[mm]	1
Fiber material		PMMA
Fiber head material		stainless steel (1.4305 / 303)
Fiber sheath material		PE
Accessories		
Items supplied		Hexagon nuts: 2 x M6
		tooth lock washers: 2
Accessories (optional)		Cutter for fibers:, E20600
Remarks		
Pack quantity		1 pcs.