




Process adapter for SMS pipe fitting

ADAPT IFM-SMS DN40/1.5" O-RG



- 1 sealing area
2 G1 Internal thread Aseptoflex Vario

EC 1935/2004 FCM FDA

Application		
Pressure rating	40 bar	4 MPa
Tests / approvals		
Pressure equipment directive	A possible classification to PED depends on the application and has to be carried out by the user / operator.	
Safety instructions	The compatibility between medium and product material has to be checked in all applications.	
Mechanical data		
Weight	[g]	139.2
Material	stainless steel (1.4435 / 316L)	
Sensor connection	G 1 Internal thread Aseptoflex Vario	
Process connection	SMS pipe fitting DN40 (1,5") Ø 55 mm	
Surface characteristics Ra/Rz of the wetted parts	Ra < 0.4 µm / Rz = 4 µm	

E33297



Process adapter for SMS pipe fitting

ADAPT IFM-SMS DN40/1.5" O-RG

Sealing	Gasket
Hygienic equipment class to DIN 11866	H4
Accessories	
Items supplied	O-rings: 1 x (24 x 2 mm), EPDM FDA compliant, E30054
Accessories (optional)	O-ring: 1 x 24 x 2, FKM, FDA compliant, E30123
	sealing ring: 1, PEEK, FDA compliant, E30124
Remarks	
Pack quantity	1 pcs.