


E40615



Process adapters clamp DIN 32676 series C (ASME BPE)

ADAPT DIN32676-C DN80



Application		
Design	for flow meter SMF	
Application	food and beverage industry; hygienic systems	
Pressure rating	10 bar	1 MPa
Tests / approvals		
Pressure equipment directive	A possible classification to PED depends on the application and has to be carried out by the user / operator.	
Safety instructions	The compatibility between medium and product material has to be checked in all applications.	

E40615



Process adapters clamp DIN 32676 series C (ASME BPE)

ADAPT DIN32676-C DN80

Mechanical data		
Weight	[g]	3897.9
Housing		tubular
Dimensions	[mm]	Ø 139 / L = 42.9
Material		stainless steel (1.4404 / 316L)
Nominal diameter		DN80 (3")
Sensor connection		ifm-specific device flange
Process connection		Clamp DIN 32676 series C (ASME BPE)
Process connection suitable for pipe standard		(DIN EN 10357 series C); (DIN EN 10357 series D); (DIN 11866 series C); (BS 4825 Part 1); (ISO 2037)
Surface characteristics Ra/Rz of the wetted parts		Ra < 0.4 µm
Accessories		
Items supplied		screws 12
Remarks		
Pack quantity		2 pcs.