


# E80416



## RFID tag

ID-TAG/22X20,5 - M8X1,25



Application		
Operating temperature (active)	[°C]	-40...85
Peak temperature (passive)	[°C]	125
Electrical data		
Operating frequency	[MHz]	13,56
Memory size	[bit]	16384
Memory type		FRAM
Chip type		MB89R118C
Number of the blocks		256
Block size	[Byte]	8
RFID standard		ISO 15693
Operating conditions		
Ambient temperature	[°C]	-40...85
Storage temperature	[°C]	-40...125
Mechanical data		
Weight	[g]	91.9
Type of mounting		Installation on metal and non-metal materials; (screw fastening ; sticking to a surface)
Dimensions	[mm]	Ø 22 / L = 20.5
Material		steel; PA 6
Remarks		
Pack quantity		5 pcs.

# E80416



## RFID tag

ID-TAG/22X20,5 -M8X1,25

### Other data

#### Reading distance when mounted on non-metal (mm)

ANT410 / DTI410	10
ANT411 / DTI411	12
ANT420 / DTI420	10
ANT421 / DTI421	17
ANT430 / DTI430	15
ANT431 / DTI431	18
ANT515 / DTI515 / DTI515	10
ANT513 / DTI513 / DTI513	22