




Wirable plug set for mobile controllers

BasicContact-Set/for CR0421



- 1 spade sockets 2.8 x 0.8 mm
- 2 spade sockets 6.3 x 0.8 mm
- 3 spade sockets 6.3 x 0.8 mm fully insulated
- 4 Contacts for automotive fuse holders
- 5 Ring terminals

Application		
Design		for BasicRelay, utilizing all connections to a BasicRelay, CR0421
Mechanical data		
Weight	[g]	85.5
Dimensions	[mm]	134.5 x 50.6 x 210



Wirable plug set for mobile controllers

BasicContact-Set/for CR0421

Accessories	
Items supplied	blade female terminals for relay contacts: 10 x (2,8 x 0,8 mm (0,5...1,0 mm²)), DIN 46340
	blade female terminals for relay contacts: 20 x (6,3 x 0,8 mm (0,5...1,0 mm²)), DIN 46340
	blade female terminals for relay contacts: 20 x (6,3 x 0,8 mm (1,0...2,5 mm²)), DIN 46340
	blade female terminals for power distributors: 20 x (6,3 x 0,8 mm (1,0...2,5 mm²)), fully insulated DIN 46245
	Contacts for automotive fuse holders: 6 x (0,5...1,5 mm²)
	Contacts for automotive fuse holders: 4 x (2,0...3,0 mm²)
	ring terminals for power supply: 1 x M6 (10 mm²), DIN 46234
	ring terminals for power supply: 1 x M8 (10 mm²), DIN 46234
	Nuts: 1 x M6, galvanized ISO 4032
	Nuts: 1 x M8, galvanized ISO 4032
Electrical connection	
terminals:	