


# EVC436



## Y connection cable

YDOAH040MSS0005H04STGH050MSS

Please see the technical note under "Downloads"



| Application                                                     |      |                                                                                |
|-----------------------------------------------------------------|------|--------------------------------------------------------------------------------|
| System                                                          |      | Free from silicone; Halogen-free; gold-plated contacts; Drag chain suitability |
| Free from silicone                                              |      | yes                                                                            |
| Electrical data                                                 |      |                                                                                |
| Operating voltage                                               | [V]  | < 60 AC/DC                                                                     |
| Protection class                                                |      | II                                                                             |
| Max. current load total                                         | [A]  | 4                                                                              |
| Overall current rating (UL)                                     | [A]  | 3                                                                              |
| Operating conditions                                            |      |                                                                                |
| Ambient temperature                                             | [°C] | -25...90                                                                       |
| Note on ambient temperature                                     |      | cULus: ...75                                                                   |
| Ambient temperature (moving)                                    | [°C] | -25...90                                                                       |
| Note on ambient temperature (moving)                            |      | cULus: ...75                                                                   |
| Storage temperature                                             | [°C] | -25...55                                                                       |
| Storage humidity                                                | [%]  | 10...100                                                                       |
| Other climatic conditions for storage according to stated class |      | 1K22/ DIN 60721-3-1                                                            |
| Protection                                                      |      | IP 65; IP 67; IP 68; IP 69K                                                    |
| Mechanical data                                                 |      |                                                                                |
| Weight                                                          | [g]  | 312                                                                            |

EVC436



Y connection cable

YDOAH040MSS0005H04STGH050MSS

|                              |                                          |                                                                                    |
|------------------------------|------------------------------------------|------------------------------------------------------------------------------------|
| Molded-body material         | TPU (urethane)                           |                                                                                    |
| Material nut                 | brass, nickel-plated                     |                                                                                    |
| Sealing material             | FKM                                      |                                                                                    |
| Number of ports splitter box | 2                                        |                                                                                    |
| Drag chain suitability       | yes                                      |                                                                                    |
| Drag chain suitability       | Bending radius for flexible applications | min. 10 x cable diameter                                                           |
|                              | Travel speed                             | max. 3.3 m/s for a horizontal travel length of 5 m and max. acceleration of 5 m/s² |
|                              | Bending cycles                           | > 5 Mio.                                                                           |
|                              | Torsional strain                         | ± 180 °/m                                                                          |

Remarks


|               |                                                 |
|---------------|-------------------------------------------------|
| Notes         | Please see the technical note under "Downloads" |
| Pack quantity | 1 pcs.                                          |

Electrical connection


Cable: 5 m, PUR, Halogen-free, black, Ø 4.3 mm; 4 x 0.34 mm² (42 x Ø 0.1 mm )

Electrical connection - plug C

Connector: 1 x M12, straight; coding: A; Moulded body: TPU (urethane), orange; Locking: brass, nickel-plated; Contacts: gold-plated; Tightening torque: 0.6...1.5 Nm



Connection



# EVC436



## Y connection cable

YDOAH040MSS0005H04STGH050MSS

### Electrical connection - Socket A/B

Connector: 2 x M12, angled; coding: A; Moulded body: TPU (urethane), orange; Locking: brass, nickel-plated; sealing: FKM;  
Contacts: gold-plated; Tightening torque: 0.6...1.5 Nm

