


I15005



Inductive area sensor

SIT-4070-CPKG/2M



1 potentiometer



Product characteristics

Electrical design	PNP
Output function	complementary
Sensing range [mm]	20...70
Housing	tubular
Dimensions [mm]	Ø 100 / L = 40

Electrical data

Operating voltage [V]	10...36 DC
Current consumption [mA]	20; (24 V)
Protection class	II
Reverse polarity protection	yes

Outputs

Electrical design	PNP
Output function	complementary
Max. voltage drop switching output DC [V]	3.5



Inductive area sensor

SIT-4070-CPKG/2M

Permanent current rating of switching output DC	[mA]	250
Switching frequency DC	[Hz]	5
Short-circuit protection		yes
Type of short-circuit protection		yes (non-latching)
Overload protection		yes

Monitoring range

Sensing range	[mm]	20...70
Sensing range adjustable		yes
Factory setting sensing range	[mm]	70
Real sensing range Sr	[mm]	70 ± 10 %

Accuracy / deviations

Correction factor		steel: 1 / stainless steel: 0.7 / brass: 0.4 / aluminum: 0.4 / copper: 0.3
Hysteresis	[% of Sr]	< 15
Switch-point drift	[% of Sr]	-15...15

Operating conditions

Ambient temperature	[°C]	-20...70
Protection		IP 65

Tests / approvals

EMC	EN 60947-5-2	
	EN 55011	class B

Mechanical data

Weight	[g]	508.5
Housing		tubular
Mounting		non-flush mountable
Dimensions	[mm]	Ø 100 / L = 40
Material		PBT

Displays / operating elements

Display	Switching status	1 x LED, yellow
---------	------------------	-----------------

Accessories

Items supplied	screws: 1 x (M10 x 50 mm)
	covers: 1

Remarks

Pack quantity	1 pcs.
---------------	--------

I15005




Inductive area sensor

SIT-4070-CPKG/2M

Electrical connection

Cable: 2 m, PVC; 4 x 0.34 mm²

Connection



BK =	Core colors :	black
BN =		brown
BU =		blue
WH =		white