


ID0038



Inductive sensor

IDC2050BARKA/SL/LS-300BL



Product characteristics

Output function		normally open
Sensing range	[mm]	50
Housing		rectangular
Dimensions	[mm]	92 x 80 x 40

Electrical data

Frequency AC	[Hz]	47...63
Operating voltage	[V]	20...140 AC / 10...140 DC
Protection class		I
Reverse polarity protection		yes

Outputs

Output function		normally open
Max. voltage drop switching output DC	[V]	6
Max. voltage drop switching output AC	[V]	6
Minimum load current	[mA]	5.5
Max. leakage current	[mA]	1.7 (140 V AC/DC)
Permanent current rating of switching output AC	[mA]	450
Permanent current rating of switching output DC	[mA]	450
Short-time current rating of switching output	[mA]	2200; (20 ms / 0,5 Hz)
Switching frequency AC	[Hz]	25
Switching frequency DC	[Hz]	25



Inductive sensor

IDC2050BARKA/SL/LS-300BL

Short-circuit protection		yes	
Type of short-circuit protection		yes (non-latching)	
Overload protection		yes	
Monitoring range			
Sensing range	[mm]	50	
Operating distance	[mm]	0...40.5; (mounted flush with mild steel (ST37))	
Accuracy / deviations			
Correction factor		steel: 1 / stainless steel: 0.85 / brass: 0.48 / aluminum: 0.46 / copper: 0.38	
Hysteresis	[% of Sr]	3...20	
Switch-point drift	[% of Sr]	-15...15	
Operating conditions			
Ambient temperature	[°C]	-25...70	
Protection		IP 67	
Tests / approvals			
EMC		EN 60947-5-2	
MTTF	[years]	352	
UL approval	Ta		0...40 °C
	Enclosure type		Type 1
	File number UL		E174191
Mechanical data			
Weight	[g]	432.5	
Housing		rectangular	
Mounting		flush mountable	
Dimensions	[mm]	92 x 80 x 40	
Material		PPE; diecast zinc; brass nickel-plated	
Displays / operating elements			
Display	Switching status		1 x LED, red
	Power		1 x LED, green
	short circuit		1 x LED, green/red alternately flashing
Accessories			
Items supplied		sealing plug: 1	
Remarks			
Pack quantity		1 pcs.	

ID0038



Inductive sensor

IDC2050BARKA/SL/LS-300BL

Electrical connection - plug

Connector: 1 x 7/8"; coding: A

