


IM8502



Inductive sensor

IME3015BFPKG/LS400LPS



Product characteristics

Output function		normally open / closed; (selectable)
Sensing range	[mm]	15
Housing		rectangular
Dimensions	[mm]	40 x 40 x 140

Electrical data

Operating voltage	[V]	10...36 DC
Current consumption	[mA]	< 15
Reverse polarity protection		yes

Outputs

Output function		normally open / closed; (selectable)
Max. voltage drop switching output DC	[V]	2.5
Minimum load current	[mA]	0
Permanent current rating of switching output DC	[mA]	250
Switching frequency DC	[Hz]	350
Short-circuit protection		yes
Overload protection		yes

Monitoring range

Sensing range	[mm]	15
Real sensing range Sr	[mm]	15 ± 10 %

IM8502



Inductive sensor

IME3015BFPKG/LS400LPS

Accuracy / deviations

Correction factor	steel: 1 / stainless steel: 0.7 / brass: 0.4 / aluminum: 0.3 / copper: 0.2	
Hysteresis	[% of Sr]	3...15
Switch-point drift	[% of Sr]	-10...10

Operating conditions

Ambient temperature	[°C]	-25...80
Protection		IP 65

Tests / approvals

EMC	EN 60947-5-2	
	EN 55011	class B

Mechanical data

Weight	[g]	226.796
Housing		rectangular
Mounting		flush mountable
Dimensions	[mm]	40 x 40 x 140
Material		PPE

Displays / operating elements

Display	Switching status	1 x LED, red
---------	------------------	--------------

Remarks

Remarks	remove jumper for normally closed	
Pack quantity	1 pcs.	

Electrical connection - plug

Connector: 1 x 7/8"; coding: A



Connection

