


KT5005



Capacitive touch sensor

KTRSHMK-RBPKG/AM/2M



Product characteristics		
Electrical design		PNP
Output function		normally open
Housing		tubular
Dimensions	[mm]	Ø 100 / L = 11
Application		
Principle of operation		static
Electrical data		
Operating voltage	[V]	12...30 DC
Current consumption	[mA]	30

KT5005



Capacitive touch sensor

KTRSHMK-RBPKG/AM/2M

Protection class	III
Reverse polarity protection	yes
Max. power-on delay time [ms]	500

Outputs

Electrical design	PNP
Output function	normally open
Permanent current rating of switching output DC [mA]	200
Short-circuit protection	yes
Overload protection	yes

Reaction times

Response time [ms]	35
--------------------	----

Operating conditions

Ambient temperature [°C]	-40...85
Protection	IP 67; IP 69K; (on the front)

Tests / approvals

MTTF [years]	394
--------------	-----

Mechanical data

Weight [g]	158.5
Housing	tubular
Dimensions [mm]	Ø 100 / L = 11
Material	actuating surface: PA Grilamid TR 90UV transparent; housing: PC/ABS black; Colored surround: PC/ABS green

Displays / operating elements

Display	Switching status	8 x LED, red
	Power	8 x LED, green

Accessories

Accessories (optional)	surround in different colors
------------------------	------------------------------

Remarks

Pack quantity	1 pcs.
---------------	--------

KT5005




Capacitive touch sensor

KTRSHMK-RBPKG/AM/2M

Electrical connection

Cable: 2 m, PUR

Connection



1	brown
3	blue
4	black