


LI2131



Sensor for point level detection

LI0132--K-00KQPKG/US/WHG



Product characteristics			
Number of inputs and outputs		Number of digital outputs: 2	
Factory setting		oils; oil-based media	
Probe length L	[mm]	132	
Application			
System		gold-plated contacts	
Media		Liquids	
Dielectric constant of the medium		> 1,8	
Recommended media		water; water-based media; oils; oil-based media	
Cannot be used for		See operating instructions, chapter "Intended use".	
Medium temperature	[°C]	-25...85; (Applications according to the German Federal Water Act (WHG) 0...85°C)	
Pressure rating		0.5 bar	0.05 MPa
Vacuum resistance	[mbar]	-500	
Electrical data			
Operating voltage	[V]	9.6...35 DC; (IO-Link: 18...30 DC)	
Current consumption	[mA]	< 15	
Protection class		III	
Reverse polarity protection		yes	
Power-on delay time	[s]	< 1	
Measuring principle		capacitive	
Inputs / outputs			
Number of inputs and outputs		Number of digital outputs: 2	



Sensor for point level detection

LI0132--K-00KQPKG/US/WHG

Outputs		
Total number of outputs	2	
Output signal	switching signal; IO-Link	
Electrical design	PNP/NPN	
Number of digital outputs	2	
Output function	OUT-OP	normally closed
Output function	OUT2	normally open / closed; (configurable)
Max. voltage drop switching output DC [V]	2.5	
Permanent current rating of switching output DC [mA]	100	
Short-circuit protection	yes	
Type of short-circuit protection	yes (non-latching)	
Overload protection	yes	
Measuring/setting range		
Factory setting	oils; oil-based media	
Probe length L [mm]	132	
Active range A [mm]	28	
Temperature measurement		
Measuring range [°C]	-25...85	
Accuracy / deviations		
Temperature measurement		
Accuracy [K]	1,5	
Resolution [K]	0.1	
Dynamic response T09 [s]	240	
Reaction times		
Response time [s]	< 0.3	
Interfaces		
Communication interface	IO-Link	
Transmission type	COM2 (38,4 kBaud)	
IO-Link revision	1.1	
SDCI standard	IEC 61131-9	
Profiles	Common - I&D	Identification and Diagnosis
SIO mode	yes	
Required master port class	A	
Process data analog	5	
Process data binary	2	
Min. process cycle time [ms]	4.5	
Supported DeviceIDs	Type of operation	DeviceID
	default	1588
Operating conditions		
Ambient temperature [°C]	-25...85	
Storage temperature [°C]	-25...85	

LI2131



Sensor for point level detection

LI0132--K-00KQPKG/US/WHG

Protection	IP 68; IP 69K; (7 days / 3 m water depth / 0.3 bar: IP 68)
------------	--

Tests / approvals

Approval	WHG; General building authority approval; overflow prevention; leakage detection	
EMC	DIN EN 61000-6-2	
	DIN EN 61000-6-3	in a closed metal tank
	DIN EN 61000-6-4	in plastic or open metal tanks
Shock resistance	DIN EN 60068-2-27	12 g (11 ms)
Vibration resistance	DIN EN 60068-2-6	5 g (10...2000 Hz)
MTTF [years]	433	
UL approval	UL approval number	H013
	File number UL	E174191

Mechanical data

Weight [g]	240
Material	PP fiber-reinforced
Materials (wetted parts)	PP
Probe diameter [mm]	16

Displays / operating elements

Display	Power	LED, green
	Switching status	LED, yellow
Operating elements	inductive programming button	

Remarks

Pack quantity	1 pcs.
---------------	--------

Electrical connection

Connector: 1 x M12; coding: A; Contacts: gold-plated




LI2131



Sensor for point level detection

LI0132--K-00KQPKG/US/WHG

Connection



OUT-OP : IO-Link
Switching output overflow prevention to the German Federal Water Act (WHG)
Switching output leakage detection to WHG (German Federal Water Act)

OUT2 : Switching output Level
Switching output temperature