


MKC3028BBPKG/G/0,3M/ZH/ASR



MK5534



Cylinder sensor with GMR cell

MKC3028BBPKG/G/0,3M/ZH/ASR

Repeatability	[mm]	< 0.1
---------------	------	-------

Operating conditions

Ambient temperature	[°C]	-25...80
Protection		IP 65; IP 67

Tests / approvals

EMC	EN 61000-4-2	- CD / 8 kV AD
	EN 61000-4-3	10 V/m
	EN 61000-4-4	2 kV
	EN 61000-4-6	10 V
	EN 55011	class B
Vibration resistance	DIN EN 60068-2-6	15 g (10...55 Hz) / 10 frequency cycles, 1 octave/minute, in 3 axes
Shock resistance	DIN IEC 68-2-27	30 g 11 ms half-sine; 1000 shocks each in every direction of the 3 coordinate axes
Vibration resistance	DIN EN 60068-2-64	10 g / (20...2000 Hz) 100 minutes, in 3 axes
MTTF	[years]	3523
UL approval	Ta	-25...55 °C
	Enclosure type	Type 1
	voltage supply	Class 2
	UL approval number	C013
	File number UL	E174191

Mechanical data

Weight	[g]	14.6
Mounting		flush mountable
Cylinder type		C-slot cylinders
Dimensions	[mm]	26.1 x 2.8 x 5.5
Material		housing: PA reinforced glass-fiber; threaded sleeve: brass; set screw: stainless steel

Displays / operating elements


Display	Switching status	1 x LED, yellow
---------	------------------	-----------------

Remarks

Pack quantity	1 pcs.
---------------	--------

Electrical connection

Connection



MK5534



Cylinder sensor with GMR cell

MKC3028BBPKG/G/0,3M/ZH/ASR

Electrical connection - plug

Cable: 0.3 m, PVC; 3 x 0.14 mm²

Connector: 3 x M8; coding: A; Locking: Knurled nut

