

O2D550



Object recognition sensor

O2DIRDKG/E1/E4/EF/GM/S/16/5A



- 1 lens
- 2 Illumination unit



Product characteristics

Type of light	Infrared light
Image resolution [px]	1280 x 960
Max. reading rate [Hz]	40

Electrical data

Operating voltage [V]	18...30 DC
Current consumption [mA]	< 300; (24V DC typical)
Max. current consumption [mA]	650; (18V DC, with switched outputs, memory stick active)
Protection class	III
Reverse polarity protection	yes
Overvoltage category	II

O2D550



Object recognition sensor

O2DIRDKG/E1/E4/EF/GM/S/16/5A

Type of light	Infrared light
Wave length [nm]	850
Image sensor	CMOS image sensor black/white

Inputs / outputs

Number of inputs and outputs	Number of digital outputs: 2
------------------------------	------------------------------

Inputs

Trigger	external; 24 V PNP/NPN (IEC 61131-2 Typ 3); TCP/IP; PROFINET; internal
---------	--

Outputs

Electrical design	PNP/NPN; (configurable)
Number of digital outputs	2; (configurable)
Output function	configurable
Max. voltage drop switching output DC [V]	1
Max. current load per output [mA]	100
Short-circuit protection	yes
Type of short-circuit protection	yes (non-latching)
Overload protection	yes

Monitoring range

Field of view size [mm]	Operating distance	Field of view		
	85	28 x 21		
	300	92 x 69		
	500	152 x 114		
	1000	302 x 227		
	1500	453 x 340		
	2000	603 x 452		
	2500	753 x 564		
Operating distance [mm]	> 85			
Image resolution [px]	1280 x 960			
Lens type	standard			
Max. reading rate [Hz]	40			

Software / programming

Parameter setting options	via PC with ifm Vision Assistant
---------------------------	----------------------------------

Interfaces

Communication interface	Ethernet
-------------------------	----------

Ethernet

Number of Ethernet interfaces	1
Transmission standard	10Base-T; 100Base-TX
Transmission rate	10 MBit/s; 100 MBit/s
Protocol	TCP/IP; PROFINET
Factory settings	IP address: 192.168.0.69
	subnet mask: 255.255.255.0 (Class C)
	gateway IP address: 192.168.0.201
	MAC address: see type label

O2D550



Object recognition sensor

O2DIRDKG/E1/E4/EF/GM/S/16/5A

Usage type		Parameter setting; Data transmission	
Operating conditions			
Ambient temperature	[°C]	-10...50	
Storage temperature	[°C]	-40...70	
Max. relative air humidity	[%]	90; (non condensing)	
Max. height above sea level	[m]	4000	
Protection		IP 65	
Degree of soiling		3	
Tests / approvals			
EMC	EN IEC 61000-6-4 radiation of interference		industrial environments
	EN IEC 61000-6-2 noise immunity		industrial environments
Shock resistance	EN 60068-2-27		50 g 11 ms / not repetitive
	EN 60068-2-27		40 g 6 ms / repetitive
Vibration resistance	EN 60068-2-6		2 g (10 ... 150 Hz)
Photobiological safety		exempt group; (EN 62471)	
Electrical safety	EN IEC 61010-2-201		electrical supply only via PELV circuits
MTTF	[years]	53	
UL approval	Ta		-10...50 °C
	Enclosure type		1
	voltage supply		Limited Energy
	File number UL		E364788
Mechanical data			
Weight	[g]	623.9	
Type of mounting		screw mounting; (bore hole M4 x 7mm)	
Dimensions	[mm]	45 x 45 x 86	
Material		housing: diecast zinc powder-coated; front lens: gorilla glass; LED window: PC; pushbuttons: POM	
Sealing material		FKM	
Tightening torque	[Nm]	2.1	
Displays / operating elements			
Display	Function		2 x LED, green
	Function		2 x LED, yellow
	Multi-function button		2 x LED, green/yellow
Operating elements	1	Multi-function button	
Accessories			
Accessories (optional)	Mounting accessories		
	Protective panes		
Remarks			
Pack quantity	1 pcs.		

O2D550




Object recognition sensor

O2DIRDKG/E1/E4/EF/GM/S/16/5A

Electrical connection - Ethernet


Connector: 1 x M12; coding: D; Moulded body: stainless steel; sealing: FKM



1	TxD+
2	RxD+
3	TxD-
4	RxD-

Electrical connection - supply

Connector: 1 x M12; coding: A; Moulded body: stainless steel



1	U+
2	trigger input
3	0 V
4	Switching output 1 configurable
5	Switching output 2 configurable / trigger output with external illumination