




Retro-reflective sensor

OSP-FBOA



Product characteristics	
Type of light	red light
Housing	rectangular
Application	
System	polarization filter
Function principle	Retro-reflective sensor
Electrical data	
Operating voltage [V]	20...250 AC/DC
Protection class	II
Reverse polarity protection	no
Type of light	red light
Wave length [nm]	660
Outputs	
Output function	light-on/dark-on mode; (programmable)
Max. voltage drop switching output DC [V]	10.5
Max. voltage drop switching output AC [V]	10.5
Minimum load current [mA]	15
Max. leakage current [mA]	6
Permanent current rating of switching output AC [mA]	250; (350 (...50 °C))

OS0033



Retro-reflective sensor

OSP-FBOA

Permanent current rating of switching output DC	[mA]	250; (350 (...50 °C))
Short-time current rating of switching output	[mA]	2200; (10 ms / 0,5 Hz)
Switching frequency AC	[Hz]	25
Switching frequency DC	[Hz]	25
Short-circuit proof		no
Overload protection		no

Monitoring range

Range referred to prismatic reflector	[m]	6; (Prismatic reflector Ø 80 E20005)
Range adjustable		yes
Polarization filter available		yes

Operating conditions

Ambient temperature	[°C]	-25...60
Protection		IP 65

Tests / approvals

EMC		EN 60947-5-2
MTTF	[years]	302

Mechanical data

Weight	[g]	277.5
Housing		rectangular
Dimensions	[mm]	80 x 28 x 95
Material		PPO modified
Lens material		glass
Lens alignment		Side sensing

Displays / operating elements

Display	Switching status	1 x LED, yellow
---------	------------------	-----------------

Electrical connection

Required protection		miniature fuse to IEC60127-2 sheet 1; ≤ 2 A; fast acting
---------------------	--	--

Accessories

Items supplied		Angle bracket: 1, E20210 screwdrivers
----------------	--	--

Remarks

Remarks		Recommendation: check the unit for reliable function after a short circuit.
Pack quantity		1 pcs.

OS0033




Retro-reflective sensor

OSP-FBOA

Electrical connection

terminals: ...1.5 mm²; Cable gland: M20 X 1.5

Connection



Note : miniature fuse to IEC60127-2 sheet 1 \leq 2 A fast acting