


OT5009



Through-beam sensor receiver

OPE-FPKG/US-100-IPF



Receiver in lower lens



Product characteristics	
Type of light	Infrared light
Housing	rectangular
Application	
Function principle	Through-beam sensor
Electrical data	
Operating voltage [V]	10...50 DC
Current consumption [mA]	30; ((24 V))
Protection class	II
Reverse polarity protection	yes
Type of light	Infrared light
Wave length [nm]	880
Outputs	
Electrical design	PNP
Output function	light-on/dark-on mode; (programmable)
Max. voltage drop switching output DC [V]	2.5
Permanent current rating of switching output DC [mA]	250
Switching frequency DC [Hz]	150
Short-circuit protection	yes
Type of short-circuit protection	yes (non-latching)

OT5009



Through-beam sensor receiver

OTE-FPKG/US-100-IPF

Overload protection	yes
---------------------	-----

Monitoring range

Transmitter / receiver	receiver
Range [m]	< 10
Range adjustable	yes

Operating conditions

Ambient temperature [°C]	-25...60
Protection	IP 65

Tests / approvals

EMC	EN 60947-5-2	
	EN 55011	class B
MTTF [years]	573	

Mechanical data

Weight [g]	161
Housing	rectangular
Dimensions [mm]	87 x 19 x 30
Material	PBT
Lens material	PMMA
Lens alignment	Side sensing

Displays / operating elements

Display	Switching status	1 x LED, yellow
	Power	1 x LED, green

Accessories

Items supplied	Angle bracket: 1, E20461 screwdrivers
----------------	--

Remarks

Pack quantity	1 pcs.
---------------	--------

Electrical connection

Connector: 1 x M12; coding: A





Through-beam sensor receiver

OPE-FPKG/US-100-IPF

Connection



Diagrams and graphs

excess gain graph

