

# PA304A



## Pressure transmitter with ceramic measuring cell

PA-010-RBR14-A-ZVG/US/ 3D/ V



### Product characteristics

|                              |                                           |              |           |
|------------------------------|-------------------------------------------|--------------|-----------|
| Number of inputs and outputs | Number of analog outputs: 1               |              |           |
| Measuring range              | 0...10 bar                                | 0...1000 kPa | 0...1 MPa |
| Process connection           | threaded connection G 1/4 Internal thread |              |           |

### Application

|                         |                             |         |
|-------------------------|-----------------------------|---------|
| System                  | gold-plated contacts        |         |
| Application             | for industrial applications |         |
| Media                   | liquids and gases           |         |
| Medium temperature [°C] | -20...60                    |         |
| Min. burst pressure     | 150 bar                     | 15 MPa  |
| Pressure rating         | 75 bar                      | 7.5 MPa |
| Type of pressure        | relative pressure           |         |

### Electrical data

|                                 |                 |
|---------------------------------|-----------------|
| Operating voltage [V]           | 9.6...32 DC     |
| Min. insulation resistance [MΩ] | 100; (500 V DC) |
| Protection class                | III             |
| Reverse polarity protection     | yes             |

### Inputs / outputs

|                              |                             |
|------------------------------|-----------------------------|
| Number of inputs and outputs | Number of analog outputs: 1 |
|------------------------------|-----------------------------|

### Outputs

|                            |               |
|----------------------------|---------------|
| Total number of outputs    | 1             |
| Output signal              | analog signal |
| Number of analog outputs   | 1             |
| Analog current output [mA] | 4...20        |

# PA304A



## Pressure transmitter with ceramic measuring cell

PA-010-RBR14-A-ZVG/US/ 3D/ V

|                                    |                        |                                                                                                                 |                     |           |
|------------------------------------|------------------------|-----------------------------------------------------------------------------------------------------------------|---------------------|-----------|
| Max. load                          | [Ω]                    | 720; (Ub = 24 V; (Ub - 9,6 V) / 20 mA)                                                                          |                     |           |
| Overload protection                |                        | yes                                                                                                             |                     |           |
| Measuring/setting range            |                        |                                                                                                                 |                     |           |
| Measuring range                    |                        | 0...10 bar                                                                                                      | 0...1000 kPa        | 0...1 MPa |
| Accuracy / deviations              |                        |                                                                                                                 |                     |           |
| Repeatability                      | [% of the span]        | < 0,1; (with temperature fluctuations < 10 K)                                                                   |                     |           |
| Characteristics deviation          | [% of the span]        | < ± 0,25 (BFSL) / < ± 0,5 (LS); (BFSL = Best Fit Straight Line; LS = limit value setting)                       |                     |           |
| Long-term stability                | [% of the span]        | < ± 0,05; (per 6 months)                                                                                        |                     |           |
| Temperature coefficient zero point | [% of the span / 10 K] | 0,2; (0...60 °C)                                                                                                |                     |           |
| Temperature coefficient span       | [% of the span / 10 K] | 0,2; (0...60 °C)                                                                                                |                     |           |
| Reaction times                     |                        |                                                                                                                 |                     |           |
| Step response time analog output   | [ms]                   | 3                                                                                                               |                     |           |
| Operating conditions               |                        |                                                                                                                 |                     |           |
| Ambient temperature                | [°C]                   | -20...60                                                                                                        |                     |           |
| Storage temperature                | [°C]                   | -40...100                                                                                                       |                     |           |
| Protection                         |                        | IP 65; IP 67                                                                                                    |                     |           |
| Tests / approvals                  |                        |                                                                                                                 |                     |           |
| ATEX marking                       |                        |  II 3D Ex tc IIIC T85°C Dc X |                     |           |
|                                    |                        |  II 3G Ex ec IIC T4 Gc X     |                     |           |
| EMC                                |                        | DIN EN 61000-6-2                                                                                                |                     |           |
|                                    |                        | DIN EN 61000-6-3                                                                                                |                     |           |
| Shock resistance                   |                        | DIN EN 60068-2-27                                                                                               | 50 g (11 ms)        |           |
| Vibration resistance               |                        | DIN EN 60068-2-6                                                                                                | 20 g (10...2000 Hz) |           |
| MTTF                               | [years]                | 555                                                                                                             |                     |           |
| Pressure equipment directive       |                        | sound engineering practice; can be used for group 2 fluids; group 1 fluids on request                           |                     |           |
| Mechanical data                    |                        |                                                                                                                 |                     |           |
| Weight                             | [g]                    | 236                                                                                                             |                     |           |
| Housing                            |                        | tubular                                                                                                         |                     |           |
| Dimensions                         | [mm]                   | Ø 30 / L = 75                                                                                                   |                     |           |
| Material                           |                        | stainless steel (1.4404 / 316L); FKM; PA; EPDM/X                                                                |                     |           |
| Materials (wetted parts)           |                        | stainless steel (1.4305 / 303); ceramics; FKM                                                                   |                     |           |
| Min. pressure cycles               |                        | 100 million                                                                                                     |                     |           |
| Tightening torque                  | [Nm]                   | 25...35; (recommended tightening torque Depends on lubrication, seal and pressure rating)                       |                     |           |
| Process connection                 |                        | threaded connection G 1/4 Internal thread                                                                       |                     |           |
| Restrictor element integrated      |                        | no (can be retrofitted)                                                                                         |                     |           |
| Remarks                            |                        |                                                                                                                 |                     |           |
| Pack quantity                      |                        | 1 pcs.                                                                                                          |                     |           |

# PA304A



## Pressure transmitter with ceramic measuring cell


PA-010-RBR14-A-ZVG/US/ 3D/ V

### Electrical connection - plug

Connector: 1 x M12; coding: A; Contacts: gold-plated



### Connection



|                   |     |    |
|-------------------|-----|----|
| 1                 | L+  |    |
| 2                 | OUT | AO |
| AO: analog output |     |    |