


SDG3"/METRIS PB DN80





Compressed air meter

SDG3"/METRIS PB DN80

Electrical design	PNP/NPN
Number of digital outputs	2
Output function	normally open / closed; (configurable)
Max. voltage drop switching output DC [V]	2.5
Permanent current rating of switching output DC [mA]	150; (per output)
Number of analog outputs	1
Analog current output [mA]	4...20; (scalable)
Max. load [Ω]	500
Pulse output	consumed quantity meter
Short-circuit protection	yes
Type of short-circuit protection	yes (non-latching)
Overload protection	yes

Measuring/setting range		
Measuring range	0.6...143.9 m/s	12...2769 m³/h
Display range	1.2...172.7 m/s	24...3323 m³/h
In steps of	0.1 m/s	1 m³/h

Pressure monitoring		
Measuring range [bar]	-1...16	
Display range [bar]	-1...20	
Resolution [bar]	0.05	
Set point SP [bar]	-0.92...16	
Reset point rP [bar]	-1...15.92	
Analog start point [bar]	-1...12.8	
Analog end point [bar]	2.2...16	
In steps of [bar]	0.01	

Volumetric flow quantity monitoring		
Measuring range	0...100000000 m³	0...353146667.2 scf
Display range	0...100000000 m³	0...353146667.2 scf
Set point SP	0.001...10000000 m³	0.05...353146667.2 scf
Pulse value	0.001...10000000 m³	0.05...353146667.2 scf
In steps of	0.0001 m³	0.005 scf
Pulse length [s]	0.002...2	

Temperature monitoring		
Measuring range	-10...60 °C	14...140 °F
Display range	-24...74 °C	-11.2...165.2 °F
Resolution	0.2 °C	0.5 °F
Set point SP	-9.7...60 °C	14.6...140 °F
Reset point rP	-10...59.7 °C	14...139.4 °F
Analog start point	-10...46 °C	14...114.8 °F
Analog end point	4...60 °C	39.2...140 °F
In steps of	0.1 °C	0.1 °F

Accuracy / deviations	
Accuracy (in the measuring range)	class 141: $\pm (3 \% \text{ MW} + 0,3 \% \text{ MEW})$; class 344: $\pm (6 \% \text{ MW} + 0,6 \% \text{ MEW})$; air quality to ISO 8573-1:2010; reference conditions: inlet pipe length $\geq 135 \text{ cm}$ outlet



Compressed air meter

SDG3"/METRIS PB DN80

pipe length ≥ 19 cm; reference temperature: 18..26 °C; standard volume flow 12...1539 m³/h; (standard volume flow DIN_ISO_2533 15 °C , 1013,25 mbar, 0 % r.H.)

Pressure monitoring

Repeatability [% of the final value]	$\pm 0,2$
Characteristics deviation [% of the final value]	$< \pm 0,5$; (BFSL = Best Fit Straight Line)
Greatest TEMPCO of the span [% MEW / 10 K]	$\pm 0,3$
Greatest TEMPCO of the zero point [% MEW / 10 K]	$\pm 0,1$

Temperature monitoring

Accuracy [K]	$\pm 0,5$; (medium flow in the limit area of the flow measurement range)
--------------	---

Reaction times

Response time [s]	0.1; (dAP = 0)
Damping process value dAP [s]	0...5

Pressure monitoring

Response time [s]	0.05
-------------------	------

Temperature monitoring

Dynamic response T05 / T09 [s]	T09 = 0,5
--------------------------------	-----------

Software / programming

Parameter setting options	hysteresis / window; normally open / closed; current/pulse output; display can be rotated and switched off; Display unit; totalizer
---------------------------	---

Interfaces

Communication interface	IO-Link	
Transmission type	COM2 (38,4 kBaud)	
IO-Link revision	1.1	
SDCI standard	IEC 61131-9 CDV	
Profiles	Common - I&D	Identification and Diagnosis
	Function	Measurement data, standard resolution
SIO mode	yes	
Required master port class	A	
Process data analog	8	
Process data binary	2	
Min. process cycle time [ms]	7.2	
Supported DeviceIDs	Type of operation	DeviceID
	default	1539

Operating conditions

Ambient temperature [°C]	0...60
Storage temperature [°C]	-20...85
Max. relative air humidity [%]	90
Protection	IP 65; IP 67

Tests / approvals

EMC	DIN EN 60947-5-9
-----	------------------

SDG450



Compressed air meter

SDG3"/METRIS PB DN80

Vibration resistance	DIN EN 68000-2-6	5 g (10...2000 Hz)
MTTF [years]	167	
Pressure equipment directive	Modul A; can be used for group 2 fluids; group 1 fluids on request	

Mechanical data

Weight [g]	11760	
Housing	rectangular	
Dimensions [mm]	160 x 141 x 200	
Material	housing sensor: PBT+PC-GF30; PPS GF40; electronics fastener: stainless steel (1.4301 / 304), stainless steel (1.4305 / 303); knurled nut: stainless steel (1.4404 / 316L); Display sealing: FKM	
Materials (wetted parts)	sensor feedthrough: stainless steel (1.4301 / 304), stainless steel (1.4404 / 316L); Sealing sensor - Pipe section: FKM; sensor tip: ceramics glass passivated; PPS GF40; Al2O3 (ceramics); acrylate; Pipe section: steel galvanized (1.0460 / 1.0565); flange: steel galvanized (1.0460 / 1.0565)	
Process connection	flange DN80 according to: DIN EN 10220	

Displays / operating elements

Display	Color display 1,44", 128 x 128 pixels	
	2 x LED, yellow	

Remarks

Remarks	MW = Measured value	
	MEW = Final value of the measuring range	
	D = inside pipe diameter	
	Measuring, display and setting ranges refer to standard volume flow according to DIN ISO 2533.	
	For information about installation and operation please see the operating instructions.	
Pack quantity	1 pcs.	

Electrical connection

Connector: 1 x M12; coding: A






Compressed air meter

SDG3"/METRIS PB DN80

Connection



- OUT1/IO-Link:

Switching output flow
Switching output temperature
Switching output pressure
Pulse output quantity meter
signal output Preset counter
- OUT2/InD:

Switching output flow
Switching output temperature
Switching output pressure
analog output flow
analog output temperature
analog output pressure
signal output Preset counter
Pulse output quantity meter
Input counter reset