

SU8200




Ultrasonic flow meter

SUR11HGBFPKG/W/US-100-IPF

Article to be discontinued
Discontinuation date: 12/31/2025

Alternative articles: SU8030

When selecting an alternative article and accessories please note that technical data may differ!



installation length with pipe adapter E40152 / E40155: 205 mm
installation length with pipe adapter E40153 / E40156: 215 mm



Product characteristics

Number of inputs and outputs	Number of digital outputs: 2	
Measuring range	0...100 l/min	0...26.42 gpm
Process connection	threaded connection G 1 external thread flat seal	

Application

System	gold-plated contacts	
Application	for industrial applications	
Installation	connection to pipe by means of an adapter	
Media	water; glycol solutions; Coolants; oils	
Note on media	low-viscosity oils with viscosity: 7...40 mm ² /s (40 °C) high-viscosity oils with viscosity: 30...68 mm ² /s (40 °C)	
Medium temperature [°C]	-10...80	
Pressure rating	16 bar	1.6 MPa

Electrical data

Operating voltage [V]	19...30 DC; (to SELV/PELV)	
Current consumption [mA]	100	
Min. insulation resistance [MΩ]	100; (500 V DC)	
Protection class	III	
Reverse polarity protection	yes	



Ultrasonic flow meter

SUR11HGBFPKG/W/US-100-IPF

Power-on delay time	[s]	10
Measuring principle		ultrasonic
Inputs / outputs		
Number of inputs and outputs		Number of digital outputs: 2
Outputs		
Total number of outputs		2
Output signal		switching signal
Electrical design		PNP
Number of digital outputs		2
Output function		normally open / closed; (configurable)
Max. voltage drop switching output DC	[V]	2
Permanent current rating of switching output DC	[mA]	250; (per output)
Short-circuit protection		yes
Type of short-circuit protection		yes (non-latching)
Overload protection		yes
Measuring/setting range		
Measuring range	0...100 l/min	0...26.42 gpm
Display range	0...120 l/min	0...31.7 gpm
Resolution	0.1 l/min	0.02 gpm
Set point SP	0.2...100 l/min	0.06...26.42 gpm
Reset point rP	0...99.8 l/min	0...26.38 gpm
Max. flow rate	[l/min]	110
In steps of	0.1 l/min	0.02 gpm
Temperature monitoring		
Measuring range	[°C]	-10...80
Resolution	[°C]	0.2
Set point SP	[°C]	-9.8...80
Reset point rP	[°C]	-10...79.8
In steps of	[°C]	0.2
Accuracy / deviations		
Flow monitoring		
Accuracy (in the measuring range)		water: $< \pm (3 \% \text{ MW} + 0,2 \% \text{ MEW})$; glycol (35 %), oil (viscosity 68 mm ² /s at 40 °C): $< \pm (5 \% \text{ MW} + 0,5 \% \text{ MEW})$
Repeatability		0,2 l/min (0,05 gpm)
Temperature monitoring		
Accuracy	[K]	0,2
Reaction times		
Flow monitoring		
Response time	[s]	0.25; (dAP = 0)
Delay time programmable dS, dr	[s]	0...50
Damping process value dAP	[s]	0...1

SU8200



Ultrasonic flow meter

SUR11HGBFPKG/W/US-100-IPF

Temperature monitoring		
Dynamic response T05 / T09	[s]	T09 = 70 (Q > 5 l/min); (water)
Software / programming		
Parameter setting options		Flow monitoring; Temperature monitoring
Operating conditions		
Ambient temperature	[°C]	-10...60
Storage temperature	[°C]	-25...80
Protection		IP 67
Tests / approvals		
EMC	EN 61000-4-2 ESD	4 kV CD / 8 kV AD
	EN 61000-4-3 HF radiated	10 V/m
	EN 61000-4-4 Burst	2 kV
	EN 61000-4-5 Surge	0,5 kV
	EN 61000-4-6 HF conducted	10 V
CPA approval	model number	001US
	accuracy class	3
	maximum allowable error	-
	Q (min)	0,3 m³/h
	Q (t)	0,54 m³/h
	Q (max)	6 m³/h
Shock resistance	DIN IEC 68-2-27	20 g (11 ms)
Vibration resistance	DIN IEC 68-2-6	5 g (10...2000 Hz)
MTTF	[years]	246
Pressure equipment directive		sound engineering practice; can be used for group 2 fluids; group 1 fluids on request
Mechanical data		
Weight	[g]	1694
Housing		rectangular
Dimensions	[mm]	130 x 100 x 80.5
Material		housing: AlMgSi0.5 anodized; sealing: FKM; PA 6.6; cover film: PA
Materials (wetted parts)		Pipe section: stainless steel (1.4404 / 316L); Process connection sealing: NBR fiber-reinforced Gasket; FKM; PES
Process connection		threaded connection G 1 external thread flat seal
Displays / operating elements		
Display	Display unit	4 x LED, green (l/min, m³/h, gal/min, gal/h)
	Display unit	2 x LED, yellow (°C / °F)
	Switching status	2 x LED, yellow
	Measured values	alphanumeric display, 4-digit
	Programming	alphanumeric display, 4-digit
Display unit		l/min; m³/h; gpm; gph; °C; °F
Accessories		
Items supplied		sealings: 2, Centellen

SU8200



Ultrasonic flow meter

SUR11HGBFPKG/W/US-100-IPF

Accessories (optional)	adapter for pipe: 1 x R 1/2, stainless steel, E40179
	adapter for pipe: 1 x R 3/4, stainless steel, E40180
	adapter for pipe: 1 x 1/2" NPT, stainless steel, E40192
	adapter for pipe: 1 x 3/4" NPT, stainless steel, E40193
	adapter for pipe: 1 x R 1/2, brass, E40152
	adapter for pipe: 1 x R 3/4, brass, E40153
	adapter for pipe: 1 x 1/2" NPT, brass, E40155
	adapter for pipe: 1 x 3/4" NPT, brass, E40156


Remarks	
Remarks	MW = Measured value
	MEW = Final value of the measuring range
	sealing: only with supplied Centellen seals
Pack quantity	1 pcs.

Electrical connection

Connector: 1 x M12; coding: A; Moulded body: brass, Optalloy-plated; Contacts: gold-plated



Connection



SU8200


Ultrasonic flow meter

SUR11HGBFPKG/W/US-100-IPF



Diagrams and graphs

Pressure loss



dP Pressure loss
Q volumetric flow quantity