


UGR501



Ultrasonic sensor

UGA02200EOKG/IO-LINK/US



- 1 LEDs
- 2 teach button



Product characteristics		
Housing		Threaded type
Electrical data		
Operating voltage	[V]	10...30 DC; (cULus - Class 2 source required)
Current consumption	[mA]	55
Protection class		III
Reverse polarity protection		yes
Power-on delay time	[s]	< 0.3
Converter frequency	[kHz]	200
Inputs / outputs		
Number of inputs and outputs		Number of digital outputs: 1
Outputs		
Total number of outputs		1
Electrical design		PNP
Number of digital outputs		1
Output function		normally open / closed; (configurable)
Max. voltage drop switching output DC	[V]	2.2
Permanent current rating of switching output DC	[mA]	100
Switching frequency DC	[Hz]	2
Short-circuit protection		yes
Overload protection		yes
Monitoring range		
Sensing range	[mm]	< 2200; (Target: 200 x 200 mm)
Angle of aperture cylindrical	[°]	14; (±2)
Accuracy / deviations		
Temperature compensation		yes
Hysteresis	[%]	< 2
Switch-point drift	[%]	-2...2
Repeatability		1 %

UGR501



Ultrasonic sensor

UGA02200EOKG/IO-LINK/US

Resolution	[mm]	1	
Notes on the accuracy / deviation		The indicated values are reached after a warm-up time of min. 20 minutes	
Software / programming			
Parameter setting options		hysteresis / window; second switch point; Switch-on and switch-off delay; switch-on operations; Teach function; light-on/dark-on mode	
Interfaces			
Communication interface		IO-Link	
Transmission type		COM2 (38,4 kBaud)	
IO-Link revision		1.1	
SDCI standard		IEC 61131-9	
Profiles	Smart Sensor - SSP 0	Generic Profiled Sensor	
	Function	Device identification	
	Function	Multiple switching signal	
	Function	Process data variable	
	Function	Device diagnosis	
	Function	Teach channel	
Required master port class		A	
Min. process cycle time	[ms]	3.2	
IO-Link process data (cyclical)	Function	bit length	
	process value	16	
	device status	4	
	binary switching information	2	
IO-Link functions (acyclical)		application specific tag; operating hours counter	
Supported DeviceIDs	Type of operation	DeviceID	
	default	699	
Note		For further information please see the IODD PDF file at "Downloads"	
Operating conditions			
Ambient temperature	[°C]	-20...70	
Storage temperature	[°C]	-30...80	
Protection		IP 67	
Tests / approvals			
EMC	EN 61000-4-2 ESD	4 kV CD / 8 kV AD	
	EN 61000-4-3 HF radiated	3 V/m	
	EN 61000-4-4 Burst	2 kV	
	EN 61000-4-6 HF conducted	3 V	
	EN 55011	class A	
Vibration resistance	EN 60068-2-6 Fc	(10-55) Hz 1 mm amplitude, vibration duration 5 min., 30 min. per axis with resonance or 55 Hz	
Shock resistance	EN 60068-2-27 Ea	30 g 11 ms half-sine; 3 shocks each in every direction of the 3 coordinate axes	
MTTF	[years]	141	
UL approval	Ta	-20...70 °C	
	voltage supply	Class 2	
	File number UL	E174191	

UGR501



Ultrasonic sensor

UGA02200EOKG/IO-LINK/US

Mechanical data		
Weight	[g]	103
Housing		Threaded type
Dimensions	[mm]	M18 x 1 / L = 97.5
Thread designation		M18 x 1
Material		stainless steel (1.4404 / 316L); PA; epoxy glass ceramics
Tightening torque	[Nm]	50


Displays / operating elements		
Display	Switching status	2 x LED, yellow
	echo	1 x LED, green
Teach function		yes

Accessories	
Items supplied	lock nuts: 2 x M18, stainless steel


Remarks	
Remarks	cULus - Class 2 source required
Pack quantity	1 pcs.

Electrical connection - connector

Connector: 1 x M12; coding: A



Connection



UGR501


Ultrasonic sensor

UGA02200EOKG/IO-LINK/US



Diagrams and graphs

Response curve



- 1: Distance
- 2: sound beam
- 3: Target 200 x 200 mm
- 4: Target Ø 25 mm
- 5: Reflector