


VSA201



Accelerometer

VIBRATION SENSOR



1 conical angle = 90°



Product characteristics

Measuring range of vibration	[g]	-250...250
Frequency range	[Hz]	1...6000
Measuring principle		capacitive

Application

Design	for connection to external diagnostic electronics VSE
Application	vibration detection

Electrical data

Operating voltage	[V]	7.2...10.8 DC
Current consumption	[mA]	< 15
Min. insulation resistance	[MΩ]	100; (500 V DC)
Protection class		III
Reverse polarity protection		yes
Type of sensor		Microelectromechanical system (MEMS)

Outputs

Analog current output	[mA]	0...10
Max. load	[Ω]	300

Measuring/setting range

Measuring range of vibration	[g]	-250...250
Frequency range	[Hz]	1...6000
Measuring principle		capacitive
Sensitivity	[μA/g]	14.2
Number of measurement axes		1

Accuracy / deviations

Linearity deviation		5 %
---------------------	--	-----

Operating conditions

Ambient temperature	[°C]	-30...125
Note on ambient temperature		UL application: < 70 °C
Storage temperature	[°C]	-30...125
Protection		IP 67; IP 68; IP 69K

VSA201



Accelerometer

VIBRATION SENSOR

Tests / approvals		
EMC	EN 61000-6-2	
	EN 61000-6-3	
Shock resistance	DIN EN 60068-2-27	50 g 11 ms
		500 g 1 ms
Vibration resistance	DIN EN 60068-2-6	20 g / 10 ... 2000 Hz
MTTF [years]		3094

Mechanical data		
Weight [g]		49
Housing		tubular
Type of mounting		M8 x 1,25
Dimensions [mm]		Ø 17 / L = 53
Material		housing: stainless steel (1.4404 / 316L)
Tightening torque [Nm]		8

Accessories	
Items supplied	washer, conical

Remarks	
Pack quantity	1 pcs.

Electrical connection	
Connector: 1 x M12; coding: A; Maximum cable length: 250 m	
	

1	L+ (+9 V)
2	I out
3	GND
4	Test