

TUBULAR INSIDE MICROMETERS

- Accuracy: $[\text{.00005}(3+n+L/2)]''$, n=number of rods, L=maximum measuring length (inch)
 $(3+n+L/50)\mu\text{m}$, n=number of rods, L=maximum measuring length (metric)
- Supplied with setting standards
- Carbide measuring faces

Inch					
Part No.	Range	Graduation	Micrometer head	Travel of micrometer head	Extension rods
3225-20	4-20"	.001"	4-5"	1"	1", 2", 4", 8"
3225-36	4-36"	.001"	4-5"	1"	1", 2", 4", 8", 16"
3225-52	4-52"	.001"	4-5"	1"	1", 2", 4", 8", 16" (2 pcs)
3225-84	4-84"	.001"	4-5"	1"	1", 2", 4", 8", 16" (4 pcs)

Metric					
Part No.	Range	Graduation	Micrometer head	Travel of micrometer head	Extension rods
3225-125	100-125mm	0.01mm	100-125mm	25mm	—
3225-500	100-500mm	0.01mm	100-125mm	25mm	25mm, 50mm, 100mm, 200mm
3225-900	100-900mm	0.01mm	100-125mm	25mm	25mm, 50mm, 100mm, 200mm, 400mm
3225-1300	100-1300mm	0.01mm	100-125mm	25mm	25mm, 50mm, 100mm, 200mm, 400mm (2 pcs)
3225-1700	100-1700mm	0.01mm	100-125mm	25mm	25mm, 50mm, 100mm, 200mm, 400mm (3 pcs)
3225-2100	100-2100mm	0.01mm	100-125mm	25mm	25mm, 50mm, 100mm, 200mm, 400mm (4 pcs)

