


Lead Free Brass Ball Valve

2 Piece, Full Port, Press Connection, Long Bonnet Neck, T-Handle, 250 WOG

JP-150LBG



FEATURES

- Dezincification Resistant Brass Alloy
- Long Bonnet Neck for Easier Access in Hard to Reach Applications
- Gland Follower and Single O-Ring Stem Design
- Blow-Out Proof Stem
- 100% Leak Tested

CERTIFICATIONS/APPROVALS

- IAPMO Certified
 - NSF/ANSI/CAN 61
 - NSF/ANSI/CAN 372
 - NSF/CAN 14
- Press End Conforms to IAPMO PS117
- MSS SP-110

PRESSURE/TEMPERATURE RATING

- 250 WOG
- 200°F

MATERIALS

No.	Part	Material
1	Body	Lead Free Brass - C46500
2	Seat	PTFE
3	Ball	304 Stainless Steel
4	O-Ring	NBR
5	Extension	Brass
6	Packing	PTFE
7	Packing Nut	Brass
8	Handle Nut	Plated Steel
9	Stem	Brass
10	O-Ring	NBR
11	Cap	Lead Free Brass - C465000
12	Handle	Plated Steel
13	O-Ring	EPDM

DIMENSIONS

Part No	Size	W	H	L
150-213G	1/2"	3.19	3.47	3.94
150-214G	3/4"	3.6	3.59	3.94