





B-7000 & BNL-7000 SERIES

FROST PROOF YARD HYDRANT FEATURES/BENEFITS

- (1) HEAVY CAST IRON HEAD simple "on" flow design BENEFIT: Stands up to abuse, "on" design has higher flow.
- (2) ONE LIFTING STRAP simple ribbed design BENEFIT: Ribbed design greatly increases strength and centered single strap eliminates side pull.
- (3) HEAVY CAST IRON HANDLE simple oversized design BENEFIT: Very easy to operate, extra room for big hands.
- (4) NO ADJUSTMENT NEEDED patented design eliminates need for adjustment (CAUTION: do not push clamp on pipe down - will damage plunger.)

BENEFIT: Design of plunger and valve body automatically adjusts itself - no field guess work.

- (5) NO PACKING GLAND REQUIRED simple fool proof design BENEFIT: No packing or packing gland to service - on site field work very simple.
- (6) EASY PLUNGER SEAL REPLACEMENT only loosen one bolt. BENEFIT: O-ring seals very easy to replace when lift out plunger.
- (7) 1" GALVANIZED RISER PIPE WITH PVC INNER PIPE BENEFIT: Sch. 80 PVC inner pipe strong non-corrosive.
- (8) 1" VALVE INLET SIZE

BENEFIT: Easy installation and better flow rate.

(9) DOUBLE BYPASS VALVE BODY provides a large volume of water and time-proven design for over seventy-five years.


BENEFIT: High water flow with economical patented design.

- (10) HYDRANT LOCKING EYE
- (11) LEVER STRAP BOLT
- (12) ONE PIECE PLUNGER ASSEMBLY
- (13) HOSE THREAD FITTING
- (14) LEVER PIVOT BOLT
- (15) LEVER STRAP PIVOT CONTROL

NOTE: This model of hydrant requires more time to drain itself. If you turn the hydrant back on when it is still draining, water will come out outlet <u>AND</u> drain hole. Hydrant is working normally.



Gives year 'round water service that drains below the frost line when shut off.



-31- Form No. 2127.5










B-7000 & BNL-7000 SERIES

PARTS LIST



FROST PROOF YARD HYDRANTS STANDARD B-7000 HYDRANTS

	Order	UPC Bar	Pipe Connection	Pipe	Overall	Approx.
	No.	Code (Qty. 1)	x Pipe Depth	Size	Length	Wt./Lbs.
\wedge	B101	6 42367 41329 3	1" x 1' Bury	1" Galv.	39.5"	11.0
$\overline{\Lambda}$	B102	6 42367 41330 9	1" x 2' Bury	1" Galv.	51.5"	13.0
\wedge	B103	6 42367 41328 6	1" x 3' Bury	1" Galv.	63.5"	15.3
\wedge	B104	6 42367 41331 6	1" x 4' Bury	1" Galv.	75.5"	17.0
\wedge	B105	6 42367 41332 3	1" x 5' Bury	1" Galv.	87.5"	19.0
\triangle	B106	6 42367 41333 0	1" x 6' Bury	1" Galv.	99.5"	21.0
\triangle	B107	6 42367 41334 7	1" x 7' Bury	1" Galv.	111.5"	23.0
\triangle	B108	6 42367 41335 4	1" x 8' Bury	1" Galv.	123.5"	25.0

NOTE: The length of hydrant you need depends on the depth the water lines are buried in your area. If water lines are buried 4' you need the B104 - 4' bury below ground 28" above ground or 6'-4" total length.

FROST PROOF YARD HYDRANTS NO-LEAD BNL-7000 HYDRANTS

	Order	UPC Bar	Pipe Connection	Pipe	Overall	Approx.
	No.	Code (Qty. 1)	x Pipe Depth	Size	Length	Wt./Lbs.
(m)	BNL101	6 42367 42347 6	1" x 1' Bury	1" Galv.	39.5"	11.0
6	BNL102	6 42367 42348 3	1" x 2' Bury	1" Galv.	51.5"	13.0
(M)	BNL103	6 42367 42349 0	1" x 3' Bury	1" Galv.	63.5"	15.3
(m)	BNL104	6 42367 42350 6	1" x 4' Bury	1" Galv.	75.5"	17.0
6	BNL105	6 42367 42351 3	1" x 5' Bury	1" Galv.	87.5"	19.0
66	BNL106	6 42367 42352 0	1" x 6' Bury	1" Galv.	99.5"	21.0
(m)	BNL107	6 42367 42353 7	1" x 7' Bury	1" Galv.	111.5"	23.0
(m)	BNL108	6 42367 42354 4	1" x 8' Bury	1" Galv.	123.5"	25.0

NOTE: The length of hydrant you need depends on the depth the water lines are buried in your area. If water lines are buried 4' you need the BNL104 - 4' bury below ground 28" above ground or 6'-4" total length.

PARTS LIST

	PARIS LIS	I	
	Part	UPC Bar	Part
	No.	Code (Qty. 1)	Description
\triangle	B-1	6 42367 41576 1	B-7000 Head Casting (Includes G-6)
(m)	BNL-1	6 42367 42440 4	B-7000 No-Lead Head Casting (Includes GNL-6)
\triangle	G-6	6 42367 11756 6	Hose Thread Adapter
66	NL-6	6 42367 10876 2	Nylon Hose Thread Adapter
(M)	GNL-6	6 42367 41048 3	No-Lead Hose Thread Adapter
66	B-10	6 42367 41577 8	Lever Casting
6	B-15S	6 42367 41578 5	Lever Bolt
66	B-15	6 42367 41579 2	Clamp Bolts
6	B-4	6 42367 41580 8	Pipe Clamp
	B-20	6 42367 41581 5	Lifting Strap
	G-15A	6 42367 41582 2	Nuts for Clamp Bolt
6	B-16	6 42367 41583 9	Lever Pivot Control
	B-50	6 42367 41584 6	Plunger Coupling
66	B-115R	6 42367 45238 4	Replacement Plunger Assembly - Parts No.
			B-115, B-50(2), OR114(2), OR116(2), 1/2" PVC 80
Ø	OR114	6 42367 00113 1	Bottom Plunger O-Rings (Std. Size 114)
	OR116	6 42367 05481 6	Top Plunger O-Rings (Std. Size 116)
\triangle	B-40	6 42367 41586 0	Valve Body
*	BNL-40	6 42367 42408 4	No-Lead Valve Body
6	B-37		1" Galvanized Pipe
0	D 05		DVO D:

B-7000 & BNL-7000 Hydrant Flow Rate

B 7000 a Bitz 7000 iiyai ane ilow ilato				
WATER SYSTEM PRESSURE	GALLONS PER MINUTE (GPM)			
	0 5 10 15 20 25 30 35 40 45 50			
10 PSI	4 GPM @ 10 PSI			
20 PSI	10 GPM @ 20 PSI			
30 PSI	12 GPM @ 30 PSI			
40 PSI	15 GPM @ 40 PSI			
60 PSI	20 GPM @ 60 PSI			
80 PSI	22 GPM @ 80 PSI			
100 PSI	26 GPM @ 100 PSI			

NOTE: Most common 1/2 hp submersible pumps output is 10GPM.



WARNING: This product can expose you to lead, which is known to the State of California to cause cancer, birth defects or other reproductive harm. (For more information go to www.p65warnings.ca.gov)



WARNING: This product meets Federal USA Drinking Water requirements but has not been specifically tested or approved as no-lead in the State of California.



ORDER NO. PKBF
UPC Bar Code (Qty. 1)
6 42367 41598 3

PARTS KIT "BF" CONTAINS

	Qty.	Part Nu	mber
(peg)	1	B-20	Lifting Strap
	1	B-15S	Lever Bolt
(FG)	2	B-15	Clamp Bolts
Ø	2	G-15A	Nuts for Clamp Bolt
(PAG)	2	OR114	Bottom Plunger O-Rings
	2	OR116	Top Plunger O-Rings