

XDS2000 Dual-Channel Series Oscilloscope Technical Specifications

Unless otherwise specified, the technical specifications applied are for XDS2000 dual-channel series only, and Probes attenuation set as 10X. Only if the oscilloscope fulfills the following two conditions at first, these specification standards can be reached.

- This instrument should run for at least 30 minutes continuously under the specified operating temperature.
- If change of the operating temperature is up to or exceeds 5°C, do a "Self-calibration" procedure .

All specification standards can be fulfilled, except one(s) marked with the word "Typical".

Performance Characteristics		Instruction		
Bandwidth	XDS2102	100 MHz		
	XDS2102A	100 MHz		
	XDS2202	200 MHz		
Vertical Resolution (A/D)	XDS2102A	12 bits		
	XDS2102	8 bits		
	XDS2202	8 bits		
Channel	2 + 1 (External)			
Waveform Refresh Rate	XDS2102A	55,000 wfms/s		
	XDS2102	75,000 wfms/s		
	XDS2202	75,000 wfms/s		
Acquisition	Mode	Normal, Peak detect, Averaging		
	Max sample rate (real time)	XDS2102A	Dual CH	500 MS/s
			Single CH	8 bits mode
	XDS2102 XDS2202	1 GS/s		
Input	Input coupling	DC, AC, Ground		
	Input impedance	1 MΩ±2%, in parallel with 15 pF±5 pF		
	Input coupling	0.001X - 1000X, step by 1 – 2 - 5		
	Max input voltage	1MΩ: ≤300 Vrms		
	Bandwidth limit	20 MHz, full bandwidth		
	Channel –channel isolation	50Hz: 100 : 1 10MHz: 40 : 1		
	Time delay between channel(typical)	150ps		
Horizontal System	Sampling rate range	XDS2102A	Dual CH	0.05 S/s ~ 500 MS/s
			Single CH	8 bits mode 0.05 S/s - 1 GS/s

Performance Characteristics		Instruction		
			12 bits mode	0.05 S/s - 500 MS/s
		XDS2102 XDS2202	0.05 S/s - 1 GS/s	
	Interpolation	(Sinx)/x, x		
	Max Record length	XDS2102A	20M.	
		XDS2102 XDS2202	40M; 80M (Optional)	
	Scanning speed (S/div)	2ns/div - 1000s/div, step by 1 - 2 - 5		
	Sampling rate / relay time accuracy	XDS2102A	± 1 ppm (Typical, Ta = +25°C)	
		XDS2102 XDS2202	± 25 ppm (Typical, Ta = +25°C)	
	Interval(ΔT) accuracy (DC - 100MHz)	Single: $\pm (1 \text{ interval time} + 1 \text{ ppm} \times \text{reading} + 0.6 \text{ ns})$; Average >16: $\pm (1 \text{ interval time} + 1 \text{ ppm} \times \text{reading} + 0.4 \text{ ns})$		
	Vertical system	Sensitivity	1 mV/div ~ 10 V/div	
Displacement		XDS2102A	± 2 V (1 mV/div - 50 mV/div); ± 20 V (100 mV/div - 1 V/div); ± 200 V (2 V/div - 10 V/div)	
		XDS2102 XDS2202	± 2 V (1 mV/div - 100mV/div); ± 200 V (200 mV/div - 10 V/div)	
Analog bandwidth		XDS2102 XDS2102A	100 MHz	
		XDS2202	200 MHz	
Single bandwidth		Full bandwidth		
Low Frequency		≥ 10 Hz (at input, AC coupling, -3 dB)		
Rise time (at input, Typical)		XDS2102 XDS2102A	≤ 3.5 ns	
		XDS2202	≤ 1.75 ns	
DC gain accuracy		XDS2102A	1 mV	3%
	2 mV		2%	
	≥ 5 mV		1.5%	
	XDS2102 XDS2202	1 mV	4%	
		≥ 2 mV	3%	

Performance Characteristics		Instruction
	DC accuracy (average)	Delta Volts between any two averages of ≥ 16 waveforms acquired with the same scope setup and ambient conditions (ΔV): $\pm(3\% \text{ rdg} + 0.05 \text{ div})$
	Waveform inverted ON/OFF	
Measurement	Cursor	ΔV , ΔT , $\Delta T \& \Delta V$ between cursors, auto cursor
	Automatic	Max, Min, PK-PK, Top, Base, Amplitude, Mean, RMS, Cycle RMS, Cursor RMS, Overshoot, Preshoot, Period, Frequency, Rise Time, Fall Time, +PulseWidth, -PulseWidth, +Duty Cycle, -Duty Cycle, Screen Duty, FRR, FRF, FFR, FFF, LRR, LRF, LFR, LFF, Delay A→B ⌘ , Delay A→B ⌘ , Phase, +PulseCount, -PulseCount, RiseEdgeCnt, FallEdgeCnt, Area, Cycle Area.
	Waveform Math	+, -, *, /, FFT, FFTrms, Intg, Diff, Sqrt, User Defined Function, digital filter (low pass, high pass, band pass, band reject)
	Decoding Type	RS232/UART, I2C, SPI, CAN
	Waveform storage	50 waveforms
	Lissajous figure	Bandwidth Phase difference
Communication port	Standard	USB, USB Host (USB storage) ; Trig Out(P/F); LAN port
	Optional	VGA port and AV port
Counter	Support	

Trigger

Performance Characteristics		Instruction	
Trigger level range	XDS2102A	Internal	± 5 div from the screen center
		EXT	± 2 V
		EXT/5	± 10 V
	XDS2102 XDS2202	Internal	± 5 div from the screen center
		EXT	± 1.5 V
		EXT/5	± 7.5 V
Trigger level Accuracy (typical)	Internal		± 0.3 div
	EXT		$\pm (10 \text{ mV} + 6\% \text{ of Set Value})$
	EXT/5		$\pm (50 \text{ mV} + 6\% \text{ of Set Value})$
Trigger displacement	According to Record length and time base		
Trigger Holdoff range	100 ns – 10 s		

50% level setting (typical)	Input signal frequency \geq 50 Hz	
Edge trigger	slope	Rising, Falling
Video Trigger	Modulation	Support standard NTSC, PAL and SECAM broadcast systems
	Line number range	1-525 (NTSC) and 1-625 (PAL/SECAM)
Pulse trigger	Trigger condition	Positive pulse: $>$, $<$, $=$ Negative pulse: $>$, $<$, $=$
	Pulse Width range	30 ns to 10 s
Slope Trigger	Trigger condition	Positive pulse: $>$, $<$, $=$ Negative pulse: $>$, $<$, $=$
	Time setting	30 ns to 10 s
Runt Trigger	Polarity	Positive, Negative
	Pulse Width Condition	$>$, $=$, $<$
	Pulse Width Range	30 ns to 10 s
Windows Trigger	Polarity	Positive, Negative
	Trigger Position	Enter, Exit, Time
	Windows Time	30 ns to 10 s
Timeout Trigger	Edge Type	Rising, Falling
	Idle Time	30 ns to 10 s
Nth Edge Trigger	Edge Type	Rising, Falling
	Idle Time	30 ns to 10 s
	Edge Number	1 to 128
Logic Trigger	Logic Mode	AND, OR, XNOR, XOR
	Input Mode	H, L, X, Rising, Falling
	Output Mode	Goes True, Goes False, Is True $>$, Is True $<$, Is True $=$
RS232/UART Trigger	Polarity	Normal, Inverted
	Trigger Condition	Start, Error, Check Error, Data
	Baud Rate	Common, Custom
	Data Bits	5 bit, 6 bit, 7 bit, 8 bit
I2C Trigger	Trigger Condition	Start, Restart, Stop, ACK Lost, Address, Data, Addr/Data
	Address Bits	7 bit, 8 bit, 10 bit
	Address Range	0 to 127, 0 to 255, 0 to 1023
	Byte Length	1 to 5
SPI Trigger	Trigger Condition	Timeout
	Timeout Value	30 ns to 10 s
	Data Bits	4 bit to 32 bit
	Data Line Setting	H, L, X
CAN Trigger	Signal Type	CAN_H, CAN_L, TX, RX

	Trigger Condition	Start of Frame, Type of Frame, Identifier, Data, ID & Data, End of Frame, Missing Ack, Bit Stuffing Error
	Baud Rate	Common, Custom
	Sample Point	5% to 95%
	Frame Type	Data, Remote, Error, Overload

General Technical Specifications

Display

Display Type	8" Colored LCD (Liquid Crystal Display)
Display Resolution	800 (Horizontal) × 600 (Vertical) Pixels
Display Colors	65536 colors, TFT screen

Output of the Probe Compensator

Output Voltage (Typical)	About 5 V, with the Peak-to-Peak voltage $\geq 1 \text{ M}\Omega$.
Frequency (Typical)	Square wave of 1 KHz

Power

Mains Voltage	100V - 240 VACRMS, 50/60 Hz, CAT II
Power Consumption	< 15 W
Fuse	2 A, T class, 250 V

Environment

Temperature	Working temperature: 0 °C - 40 °C Storage temperature: -20 °C - 60 °C
Relative Humidity	≤ 90%
Height	Operating: 3,000 m Non-operating: 15,000 m
Cooling Method	Fan cooling

Mechanical Specifications

Dimension	340 mm× 177 mm×90 mm (L*H*W)
Weight	Approx. 2.6 kg (without accessories)

Interval Period of Adjustment:

One year is recommended for the calibration interval period.



7007020100057

V1.1.2

※: The illustrations, interface, icons and characters in the user manual may be slightly different from the actual product. Please refer to the actual product.