

Argus Track

4K Dual-Lens Wi-Fi Solar/Battery Camera with Auto-Zoom Tracking

- Dual View: Full & Close-up Views
- Pan, Tilt & 6X Hybrid Zoom
- 4K 8MP UHD
- Person/Vehicle/Animal Detection



Specifications

Video & Audio	
Image Sensor	1/2.7" CMOS sensor
Resolution	3840×2160(8 megapixels)@15fps 1920×1080(2 megapixels)@15fps
Lens	
Video Compression	H.264/H.265
Field of View	Lens 1: Horizontal: 105°; Vertical: 55°; Diagonal: 123° Lens 2: Horizontal: 43°; Vertical: 25°; Diagonal: 49.5°
Infrared Night Vision	Up to 30 meters (100ft); LED: 2pcs/2.15W/850nm (Auto-switching with IR-cut filter)
Color Night Vision	With spotlights: 2pcs/6000K/295 Lumen (15Meters, Adjustable)
Frame Rate	Main stream: 10fps - 15fps (default: 15fps) Sub stream: 10fps - 15fps (default: 15fps)

Code Rate	Main stream: 1024Kbps - 4096Kbps (default: 2048Kbps) Sub stream: 64Kbps - 672Kbps (default: 672Kbps)
Audio	Two-way audio
Power	
Battery	4800mAh rechargeable battery (Battery life varies based on settings, usage & temperature.)
Solar	Reolink Solar Panel 2 (6W)
Interface	
Power Port	USB-C port
SD Card Slot	Supports Max. 512GB microSD card
Reset Button	Yes
Audio In/Out	Built-in microphone and speaker
Pan & Tilt	
PT Angle(Max.)	Pan: 355°, Tilt: 50° (PT speed is configurable)
Preset Points	Supports 1 guard position & up to 32 preset positions
Patrol	Not Supported
Power-off Memory Function	YES
Auto Tracking	YES
Wi-Fi	
Wireless Standard	IEEE 802.11 a/b/g/n
Operating Frequency	2.4 GHz/5GHz
Wireless Security	WPA/WPA2
Software	
OS Supported	PC: Windows, Mac OS; Smartphone: iOS, Android
Protocols & Standards	SSL, TCP/IP, UDP, UPNP, SMTP, NTP, P2P

User Access	Max. 12 simultaneous streams (2 main & 10 sub streams)
Other Features	
Smart Alarm	PIR detection; motion detection; person detection; vehicle detection; animal detection
PIR Detecting Distance	Adjustable, up to 11m (36ft)
PIR Detecting Angle	120° horizontal
Recording Modes	Motion recording
Time Lapse	YES
Smart Home Compatibility	Google Assistant
Cloud Storage	Supports Reolink Cloud (available in selected countries)
Working Environment	
Operating Temperature	-10°C~55°C (14°F~131°F)
Operating Humidity	10% ~ 90%
Weatherproof	YES
Mechanical	
Dimensions	Ø85*84*118mm
Weight Battery Included	476g
Warranty	
Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/ .

Gallery & Specs



1. IR LEDs
2. Spotlight
3. Status LED
4. Daylight Sensor
5. Built-in Mic
6. PIR Sensor



1. Power Switch
2. microSD Card Slot
3. Reset Button
4. USB-C Port

