

CX820

4K 8MP ColorX PoE camera with true full-color night vision, F1.0 super aperture, 1/1.8" sensor, smart detection, 2-way audio, customizable siren, etc.

- F1.0 Super Aperture
- HDR Technology
- True Full-Color Night Vision in the Dimmest Light
- Person/Vehicle/Animal Detection



Specifications

| Video & Audio | |
|--------------------------|---|
| Image Sensor | 1/1.8" CMOS sensor |
| Resolution | 3840*2160 (8Megapixels)@25FPS |
| Lens | f=4mm F=1.0, with IR Cut |
| Video Compression | H.265/H.264 |
| Field of View | Horizontal: 93.2° Vertical: 48.2° Diagonal: 111.6° |
| Day & Night | Color night vision |
| Infrared Night Vision | N/A |
| Color Night Vision | 3pcs/2.8W/3000K/400Lumens |
| Frame Rate | Main stream: 2fps - 25fps(default: 25fps) Sub stream: 4fps - 15fps(default: 10fps) |
| Code Rate | |

| | |
|---------------------------|--|
| | Main stream:1024Kbps -8192Kbps(default: 6144Kbps) Sub stream: 64Kbps - 512Kbps(default: 256Kbps) |
| Audio | Two-way audio |
| Power Requirements | |
| PoE | IEEE 802.3af, 48V Active |
| DC Power | DC 12.0V 1A, <12W |
| Interface | |
| Power Port | DC power port |
| Ethernet Port | One 10M/100Mbps RJ45 |
| SD Card Slot | Supports Max. 256GB microSD card |
| Reset Button | YES |
| Audio In/Out | Built-in microphone & speaker |
| Software | |
| Browsers Supported | Edge, Chrome, Firefox, Safari |
| OS Supported | PC: Windows, Mac OS; Smartphone: iOS, Android |
| Protocols & Standards | HTTPS, SSL, TCP/IP, UDP, HTTP, IPv4, UPnP, RTSP, RTMP, SMTP, NTP, DHCP, DNS, DDNS, FTP, P2P |
| Software Features | |
| Maximal User Access | 20 Users (1 admin account & 19 user accounts); Support up to 12 simultaneous video streams (10 substreams & 2 mainstreams) |
| Other Features | |
| Smart Alarm | Motion detection/person detection/vehicle detection/animal detection |
| Recording Modes | Motion-triggered recording (default); Scheduled recording; 24/7 recording |
| HDR | YES |
| Time Lapse | YES |

| | |
|----------------------------|---|
| Smart Home Compatibility | Google Assistant |
| Working Environment | |
| Temperature | Operating temperature: -10°C~+55°C (14°F~131°F) |
| Humidity | Operating humidity: 10% ~ 90% |
| Weatherproof | IP67 |
| Mechanical | |
| Dimensions | Φ 117.4x 103.8mm |
| Weight | 515g |
| Warranty | |
| Limited Warranty | 2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/ |

Gallery & Specs



1. Mount
2. microSD Card Slot
3. Aluminum Casing
4. Cable Hole
5. Speaker
6. Microphone



1. Spotlight
2. Lens



Only Manual Rotation



1. Power Port
2. Reset Button
3. Network Port
4. Waterproof Lid

www.reolink.com