

Reolink TrackMix (Battery)

Battery-powered dual-lens camera with smart detection & auto-zoom tracking

- Dual-View Display
- Auto-Zoom Tracking
- Battery/Solar Powered

Specifications

Video & Audio	
Image Sensor	1/3" CMOS Sensor
Video Resolution	Up to: 2560 x 1440 (4.0 Megapixels) at 15 frames/sec
Lens	f=2.8 mm, F=1.6; f=8 mm, F=1.6
Video Compression	H.264/H.265
Field of View	Horizontal: 96°-38°; Vertical: 55°-21°
Zoom Mode	6x hybrid zoom
Day & Night	IR-cut filter with auto-switching
Infrared Night Vision	Up to 15 Meters (50ft) (LED: 2pcs/850nm)
Color Night Vision	Spotlight: 1pcs/6500K/450 Lumens
Audio	Two-way audio
Power	
Battery	10400mAh rechargeable battery (Battery life varies based on settings, usage & temperature)

Solar	Reolink Solar Panel 2
DC Power	5V/2A
Interface	
Power	USB Type-C port
System	Reset Button
Storage	microSD card slot (Max. 128GB)
Audio	Built-in microphone and speaker
Pan & Tilt	
Pan &Tilt	Pan: 355°, Tilt: 0°~90°; (Speed can be set)
Preset Points	32
Auto Tracking	Support
Wi-Fi	
Wireless Standard	IEEE 802.11a/b/g/n
Operating Frequency	2.4GHz/5GHz
Wireless Security	WPA-PSK/WPA2-PSK
Software Features	
Frame Rate	Mainstream: 10fps - 15fps; Substream: 10fps - 15fps
Code Rate	Mainstream: 1024Kbps - 4096Kbps; Substream: 64Kbps - 512Kbps
OS Supported	PC: Windows, Mac OS; Smartphone: iOS, Android
Smart Alarm	PIR detection/Human detection/ Vehicle detection/Pet detection
Record Mode	Motion triggered recording
Protocols & Standards	SSL, TCP/IP, UDP, UPNP, SMTP, NTP, P2P
Maximum User Access	Support up to 12 simultaneous video streams (10 substreams & 2 mainstreams)

Work with	Google assistant, Reolink Cloud
Working Environment	
Operating Temperature	Operating temperature: -10°C~+55°C (14°F~131°F)
Operating Humidity	Operating humidity: 20% ~ 85%
Weatherproof	IP65
Size & Weight	
Dimensions	228.2*147*129mm
Weight	1.4KG
Warranty	
Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/

Gallery & Specs



1. Spotlight
2. Infrared LED
3. Lens
4. Status LED
5. Daylight Sensor
6. PIR Sensor



1. microSD Card Slot



www.reolink.com